

**Wandcontactdoos met randaarde 16 A 250 V~ met opdruk "EDV"**  
**System 55**



| Specificatie                                                                                            | Art. nr. | VE  | EUR/stuk excl. BTW | PS | EAN           |
|---------------------------------------------------------------------------------------------------------|----------|-----|--------------------|----|---------------|
|  crème wit glanzend   | 4458 01  | 1/5 | 10,80              | 01 | 4010337093176 |
|  zuiver wit glanzend | 4458 03  | 1/5 | 10,80              | 01 | 4010337093190 |
|  zuiver wit mat      | 4458 27  | 1/5 | 10,80              | 01 | 4010337093213 |
|  antraciet           | 4458 28  | 1/5 | 12,36              | 11 | 4010337093220 |
|  kleur aluminium     | 4458 26  | 1/5 | 17,96              | 11 | 4010337093206 |
|  zwart mat           | 4458 005 | 1/5 | 17,96              | 11 | 4010337093169 |
|  grijs mat           | 4458 015 | 1/5 | 17,96              | 11 | 4010337093183 |

## Kenmerken

- Geaarde draagring.

## Technische gegevens

|                                               |                                             |
|-----------------------------------------------|---------------------------------------------|
| Inbouwdiepte:                                 | 32 mm                                       |
| Kabelmateriaal:                               | Stijf en flexibel                           |
| Aansluitingdoorsnede<br>- voor geleiders van: | 1,5 mm <sup>2</sup> tot 2,5 mm <sup>2</sup> |

---

## Aanwijzingen

- Met verhoogde contactdruk van de aardbeugel, getest door TNO.
-