

PRODUCT DATASHEET

Type: Stapaflex-FPR
Art. Nr.: 30011



9120054170731

Short description

Installation hose, Stapaflex, asphalt installation, DN 20



*** Image missing:
/Data/Environments/000039/Attachment/Bijlage/PRD/Product/CHR/DE/etherma-db-30011-de.pdf ***

Product Description

Armored installation conduit for laying sensors and connection cables in asphalt surfaces. The hose is resistant to the high temperatures when applying asphalt floor coverings.

ETIM characteristics

Material	Aluminium	Inner diameter	16 Millimetre
Material quality	Other	Outer diameter	20 Millimetre
Surface protection	Untreated	Operating temperature	220 220 Degrees celsius
Quality of surface coating	Other		
Surface polished	✗		
Surface brushed	✗		
Model	Pliable corrugated		
Connection 1	Other		
Connection 2	Other		
Colour	Grey		
Flush-mounted installation	✓		
Surface mounting	✗		
Suitable for concrete installation	✓		
Machine and systems installation	✓		
Suitable for underfloor installation (bitumen, hot asphalt)	✓		
Suitable for underfloor installation (screed)	✓		
Suitable for outdoor installation	✓		
Suitable for installation on wood	✓		
Suitable for hollow wall installation	✓		
Suitable for underground installation	✓		
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)		

Created on: 09/10/2024