

## PRODUCT DATASHEET

**Type:** RLH-15-24  
**Art. Nr.:** 34442



### Short description

Heating loop for screed installation, 15W/m, 24m, 358W, 230V



### Product Description

The RLH heating loops are ideal for free laying in concrete and flowing screeds in indoor areas for temperature control of floors. The installation distance enables application-oriented installation for every room. The factory-assembled heating loop with 15 or 20 W/m consists of a dipole heating conductor and a permanently water-resistant, non-heating connection cable (cold end) 3 m long. The connecting cable can be produced in the desired length for an additional charge. Temperature-resistant up to 90 °C, system design: CE-compliant, protection class: IP X7, protective measure: residual current circuit breaker 30 mA, heating conductor design in accordance with VDE NH2G2GQUY, min. bending radius: 5 d.

### ETIM characteristics

<b>Cable type</b>	Dual core	<b>Nominal voltage</b>	230 Volt
<b>Constant power</b>	✓	<b>Max. hold temperature</b>	90 Degrees celsius
<b>Self-limiting</b>	✗	<b>Heating capacity</b>	15 Watt per metre
<b>Screening</b>	Foil	<b>Diameter</b>	6 Millimetre
<b>Material screening</b>	Aluminium	<b>Height</b>	0 Millimetre
<b>Surface treatment screening</b>	Other	<b>Width</b>	0 Millimetre
<b>Colour</b>	Black	<b>Length</b>	24 Metre
<b>Application</b>	Other		

Created on: 09/10/2024