

PRODUCT DATASHEET

Type: PG-ST
Art. Nr.: 34551



9120015727141

Short description

Connecting cable with plug for KST, L 0.5m



Product Description

The connecting cable is used for through-wiring KST bench spotlights.

ETIM characteristics

Connection 1	CEE plug (IEC 60309)	Number of cores	3
Cable entry connection 1	Straight	Nominal cross section conductor	1.5 Square millimetre
Connection type according to IEC 60320, connection 1	Other	Length	0.5 Metre
Connection 2	CEE coupling (IEC 60309)	Temperature resistance	70 70 Degrees celsius
Cable entry connection 2	Straight	Nominal current	16 Ampere
Connection type according to IEC 60320, connection 2	Other	Nominal voltage	230 230 Volt
System-oriented connector system	✓	Frequency	50 50 Hertz
Material outer sheath	Polyvinyl chloride (PVC)	Outer diameter approx.	6 Millimetre
Colour outer sheath	Black		
Spiralized cable	✗		
With protective conductor	✓		
Degree of protection (IP)	Other		
Oil resistant according to EN IEC 60811-404	✗		
With cord switch	✗		
Reaction-to-fire according to EN 13501-6: Class	None		
Reaction-to-fire according to EN 13501-6: Smoke production	None		
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None		
Reaction-to-fire according to EN 13501-6: Acidity	None		

Created on: 09/10/2024