

## PRODUCT DATASHEET

**Type:** KB-200  
**Art. Nr.:** 34696



### Short description

Fixed connection cassette for wall radiator CP and CL



### Product Description

Fixed connection cassette for easy fixed connection of CP and CL heating panels.

### ETIM characteristics

|                                                    |                 |                                         |                       |
|----------------------------------------------------|-----------------|-----------------------------------------|-----------------------|
| <b>Mounting method</b>                             | Surface mounted | <b>Number of connection clamps</b>      | 2                     |
| <b>Shape</b>                                       | Rectangular     | <b>Max. conductor cross section</b>     | 1.5 Square millimetre |
| <b>Extension possible</b>                          | ✓               | <b>Length</b>                           | 120 Millimetre        |
| <b>Type of inlet</b>                               | Cable           | <b>Width</b>                            | 100 Millimetre        |
| <b>Material</b>                                    | Plastic         | <b>Depth</b>                            | 25 Millimetre         |
| <b>Halogen free</b>                                | ✓               | <b>Material plate thickness cabinet</b> | 2 Millimetre          |
| <b>Surface protection</b>                          | Untreated       | <b>Number of inlets</b>                 | 1                     |
| <b>Colour</b>                                      | White           | <b>RAL-number</b>                       | 9001                  |
| <b>Degree of protection (IP)</b>                   | IP24            | <b>Rated insulation voltage Ui</b>      | 0 Volt                |
| <b>Degree of protection (NEMA)</b>                 | Other           | <b>Nominal voltage</b>                  | 230 Volt              |
| <b>With cover</b>                                  | ✓               | <b>Operating temperature</b>            | 5 30 Degrees celsius  |
| <b>Cover attachment</b>                            | Screwed         | <b>Rated current</b>                    | 16 Ampere             |
| <b>With transparent cover</b>                      | ✗               |                                         |                       |
| <b>Sealable</b>                                    | ✗               |                                         |                       |
| <b>Circuit integrity</b>                           | None            |                                         |                       |
| <b>Impact strength</b>                             | Other           |                                         |                       |
| <b>Connection type</b>                             | Other           |                                         |                       |
| <b>Explosion-tested version</b>                    | ✗               |                                         |                       |
| <b>For Ex-zone gas</b>                             | None            |                                         |                       |
| <b>For Ex-zone dust</b>                            | None            |                                         |                       |
| <b>Compliant with BS 6220</b>                      | ✗               |                                         |                       |
| <b>Maintenance free in accordance with BS 5733</b> | ✗               |                                         |                       |

Created on: 09/10/2024