

PRODUCT DATASHEET

Type: LAVA2-GLAS-180-DYL

Art. Nr.: 39662



9120061391266

Short description

infrared heating panel with customer motif, glass, 50x63cm, 180W



Product Description

The LAVA 2.0 DYL infrared heater offers the possibility of customizing an infrared heater. Whether a vacation photo or company logo, the customer motif is applied. And you won't even notice that the motif devices are actually modern infrared heaters. The LAVA 2.0 DYL is suitable for wall mounting and can be mounted vertically or horizontally, depending on the motif. The 6 mm thick safety glass and 2 temperature limiters ensure maximum safety at all times. The innovative technology makes the glass a very good radiation emitter. In conjunction with the even heat distribution on the surface, the optimally insulated rear guarantees high radiation efficiency and therefore maximum infrared heat radiation to the front of the room. The frameless construction ensures a modern design. There are 4 outputs to choose from. The practical Plug & Play box at the rear of all LAVA 2.0 models enables simple installation of a control unit, whether directly on the appliance, by radio or by means of a wired controller. On/off switch, surface temperature: max. 70 °C, protection class: IP X4, surfaces: 6 mm toughened safety glass, pluq connection cable: 1 m, TÜV, CE-compliant, 230 V.

ETIM characteristics

Type of IR radiation Mounting method Mounting direction Suitable for ceiling mounting	IR-C Surface mounting Horizontal/vertical	Power consumption Supply voltage Frequency supply voltage Max. surface temperature
Degree of protection (IP)	IPX4	Height
Colour	Multi-coloured	Width
With imprint	✓	Depth
With room temperature controller	×	RAL-number
With mounting material	✓	Colour temperature
With framework	×	
Material framework	Other	
Colour framework	Other	
Surface treatment	Other	
Surface structure front- side panel	Smooth	
With lighting cove	×	
Dimmable	×	

Created on: 09/10/2024

180 Watt 230|230 Volt 50|50 Hertz

70 Degrees celsius

630 Millimetre 500 Millimetre 61 Millimetre

n

0|0 Kelvin

Light outlet

Direct

Tel.: +49 2562 / 81 97 00 Mail: office.de@etherma.com Web: www.etherma.com