

## PRODUCT DATASHEET

**Type:** LAVA2-CERAMIC-1000-CL  
**Art. Nr.:** 39693



9120061391563

### Short description

infrared heating panel, ceramic, calacatta, 160x63cm, 1000W, 230V



### Product Description

The LAVA 2.0 designer infrared heaters are particularly efficient and energy-saving. The 6 mm thick surface material made of safety glass, special ceramic or fine stone and 2 temperature limiters in all panels guarantee safety in use at all times. The innovative technology makes the surfaces a very good radiation emitter. In conjunction with the even heat distribution on the surface, the optimally insulated rear guarantees high radiation efficiency and therefore maximum infrared heat radiation to the front of the room. The frameless construction ensures a modern design. There are four surfaces (STEEL / GLASS / CERAMIC / STONE) and up to 6 outputs to choose from. The practical Plug & Play box at the rear of all LAVA 2.0 models enables simple installation of a control unit, whether directly on the appliance, by radio or using a wired controller. As LAVA DYL 2.0 - Design Your LAVA, it is possible to apply your own designs, pictures and photos to the LAVA GLAS 2.0 or LAVA BATH 2.0. On/off switch, surface temperature: max. 95 °C, vertical and horizontal wall mounting possible, protection class: IP X4, surfaces: sheet steel, 6 mm toughened safety glass, 6 mm special ceramic or 6 mm fine stone, plug connection cable: 1 m, test mark: TÜV, CE compliant.

### ETIM characteristics

|                                           |                     |                                 |                    |
|-------------------------------------------|---------------------|---------------------------------|--------------------|
| <b>Type of IR radiation</b>               | IR-C                | <b>Power consumption</b>        | 1000 Watt          |
| <b>Mounting method</b>                    | Surface mounting    | <b>Supply voltage</b>           | 230 230 Volt       |
| <b>Mounting direction</b>                 | Horizontal/vertical | <b>Frequency supply voltage</b> | 50 50 Hertz        |
| <b>Suitable for ceiling mounting</b>      | ✗                   | <b>Max. surface temperature</b> | 95 Degrees celsius |
| <b>Degree of protection (IP)</b>          | IPX4                | <b>Height</b>                   | 630 Millimetre     |
| <b>Colour</b>                             | Other               | <b>Width</b>                    | 1600 Millimetre    |
| <b>With imprint</b>                       | ✗                   | <b>Depth</b>                    | 61 Millimetre      |
| <b>With room temperature controller</b>   | ✗                   | <b>RAL-number</b>               | 0                  |
| <b>With mounting material</b>             | ✓                   | <b>Colour temperature</b>       | 0 0 Kelvin         |
| <b>With framework</b>                     | ✗                   |                                 |                    |
| <b>Material framework</b>                 | Other               |                                 |                    |
| <b>Colour framework</b>                   | Other               |                                 |                    |
| <b>Surface treatment</b>                  | Other               |                                 |                    |
| <b>Surface structure front-side panel</b> | Smooth              |                                 |                    |
| <b>With lighting cove</b>                 | ✗                   |                                 |                    |
| <b>Dimmable</b>                           | ✗                   |                                 |                    |
| <b>Light outlet</b>                       | Direct              |                                 |                    |

Created on: 09/10/2024