

PRODUCT DATASHEET

Type: LAVABATH2-ST-700-W

Art. Nr.: 40564



9120061394373

Short description

Bathroom infrared heating panel, metal, white, 160x63cm, 700W, 230V



Product Description

The LAVA BATH 2.0 is the perfect source of warmth for your bathroom. The strong surface material made of toughened safety glass, Corian or fine stone and 2 temperature limiters in all panels guarantee safety in use at all times. The innovative technology makes the surfaces a very good radiation emitter. In conjunction with the even heat distribution on the surface, the optimally insulated rear guarantees a high degree of radiation efficiency and therefore maximum infrared heat radiation to the front of the room - once switched on, the panel is heated to a maximum of 80 °C depending on the surface and provides cozy warmth within a very short time. And thanks to the included towel holder, it also keeps towels cozy and warm. The frameless construction ensures a modern design. There is a choice of four surfaces (STEEL / GLASS / STONE / CORIAN) and up to five power levels. Up to two additional towel rails can also be attached to the appliance. The practical Plug & Play box on the back makes it easy to install a control unit, whether directly on the appliance, by radio or using a wired controller. Incl. one chrome-plated towel rail open on one side, On/Off switch, surface temperature: max. 80 °C, vertical wall mounting, protection rating: IP X4, surfaces: sheet steel, 6 mm toughened safety glass, 6 mm fine stone or 12 mm Corian, plug connection cable: 1 m, test mark: CE compliant.

ETIM characteristics

Type of IR radiation	IR-C	Power consumption
Mounting method	Surface mounting	Supply voltage
Mounting direction	Vertical	Frequency supply vol
Suitable for ceiling mounting	×	Max. surface tempera
Degree of protection (IP)	IPX4	Height
Colour	White	Width
With imprint	×	Depth
With room temperature controller	×	RAL-number
With mounting material	✓	Colour temperature
With framework	×	
Material framework	Other	
Colour framework	White	
Surface treatment	Other	
Surface structure front- side panel	Smooth	
With lighting cove	×	
Dimmable	×	

Direct

Power consumption	700 Watt
Supply voltage	230 230 Volt
Frequency supply voltage	50 50 Hertz
Max. surface temperature	80 Degrees celsi
Height	1600 Millimetre
Width	630 Millimetre
Depth	57 Millimetre
RAL-number	9016
Colour temperature	0 0 Kelvin

Created on: 09/10/2024

Light outlet

Tel.: +49 2562 / 81 97 00 Mail: office.de@etherma.com Web: www.etherma.com