

PRODUCT DATASHEET

Type: LAVA-BASIC-750DM-NA
Art. Nr.: 40886



9120105410595

Short description

Infrared heating panel, wall/ceiling, nano-anthr., 124,5x62cm, 750W

**Product Description**

The LAVA BASIC-DM is an infrared heating system that is only 22 mm deep, suitable for both ceiling and wall mounting, and generates infrared radiant heat using a special magnetic field-free heating element. Unlike conventional heating devices, it not only warms the air, but also all persons and objects in the room. In addition, the devices are excellently suited as full or zone heating. When installed in the false ceiling, the heating is fully integrated into the ceiling. By mounting the ceiling, the space can be optimally utilized, and damage to the heater is avoided. Available in the colors traffic white RAL 9016, nano anthracite RAL 7016 and in the LAVA BASIC-DM RAL version in all RAL colors and in up to 6 outputs (350-1500 W). Finely structured surface, body: steel housing, protection type: IP 21, surface temperature: ceiling mounting max. 120 °C / wall mounting max. 95 °C, mounting depth: 52 mm, certification mark: TÜV, CE compliant; connection cable: 1 m, 3 x 1.5 mm² without plug and without plug & play connection. 230 V.

ETIM characteristics

Type of IR radiation	IR-C	Power consumption	750 Watt
Mounting method	Surface mounting	Supply voltage	230 230 Volt
Mounting direction	Horizontal/vertical	Frequency supply voltage	50 50 Hertz
Suitable for ceiling mounting	✓	Max. surface temperature	120 Degrees celsius
Degree of protection (IP)	IP21	Height	620 Millimetre
Colour	Grey	Width	1245 Millimetre
With imprint	✗	Depth	52 Millimetre
With room temperature controller	✗	RAL-number	7016
With mounting material	✓	Colour temperature	0 0 Kelvin
With framework	✗		
Material frame	Other		
Colour framework	Other		
Surface treatment	Other		
Surface structure front-side panel	Smooth		
With lighting cove	✗		
Dimmable	✗		
Light outlet	Direct		

Created on: 22/10/2024