

PRODUCT DATASHEET

Type: eTRACE-30CHT
Art. Nr.: 40909



Short description

Constant heating tape for roof and box gutters, 30W/m



Product Description

The eTRACE-30CHT constant heating tape is ideal for gutter heating of box gutters. The heating tape is soft-elastic, made of an insulated, flexible tape element and with a silicone sheath. Designed in accordance with VDE regulations with soldered resistance wire. It lies flat in the gutter and reliably prevents snow from tunneling. In order to achieve the lowest possible operating costs for gutter heating, it is necessary for the heating tape to have optimum contact with the gutter. Constant heating tapes must not be installed in plastic gutters and drains. Nominal temperature: +200 °C, min. installation temperature: -60 °C, bending radius: 25 mm, CE compliant, can be cut to length every 60 cm, max. heating circuit length at 16 A is 58 m.

ETIM characteristics

Cable type	Dual core	Nominal voltage	230 Volt
Constant power	✗	Max. hold temperature	200 Degrees celsius
Self-limiting	✓	Heating capacity	30 Watt per metre
Screening	Foil	Diameter	0 Millimetre
Material screening	CuNi	Height	8 Millimetre
Surface treatment screening	None	Width	11 Millimetre
Colour	Black	Length	1 Metre
Application	Gutter		

Created on: 09/10/2024