

PRODUCT DATASHEET

Type: ET-AQUA-WSP-10D
Art. Nr.: 41115



9120105412025

Short description

Pressure resistant hot water storage, 10l, 230V



Product Description

The ETEHRMA AQUA WSP pressure-resistant hot water storage tank is suitable for under-sink installation under washbasins in a closed system. The stainless steel inner tank guarantees maximum safety and does not require regular replacement of an anode. The connection to the tap is made via a safety group (not included in the scope of delivery). The pressure-resistant design means that several tapping points can be connected. An unpressurized connection is also possible. Capacity: 5 or 10 l, rated output: 2000 W, UT installation, water pressure: max. 6 bar, color: white, protection class: IP 24, water connection: Gz 1/2, EEK: A, 230 V.

ETIM characteristics

Material boiler tank	Stainless steel	Tank volume	10 Litre
Material casing	Plastic	Nominal power	2 Kilowatt
Three-phase model	✗	Connection voltage	220 240 Volt
Frequency	50/60 Hz	Heat-up time from 10 °C to 65 °C	11 Minute
Design form	Built-under	Tap capacity at 60 °C, continuous	6 Litre per minute
Plinth boiler	✗	Max. operating pressure	6 Bar
With off-peak electricity circuit	✗	Height	470 Millimetre
Low-pressure model	✓	Width	329 Millimetre
Hot fill	✓	Depth	239 Millimetre
Duo model	✗	Diameter	0 Millimetre
Suitable for boiling water	✗	Outer pipe diameter cold tap water	12.7 Millimetre
With watercooler	✗	Outer pipe diameter hot tap water	12.7 Millimetre
Wall set-up	✗	Outer pipe diameter circulation pipe	12.7 Millimetre
Horizontal positioning	✗	Outer pipe diameter drainage connection	12.7 Millimetre
Vertical positioning	✓	η_{wh} (water heating energy efficiency)	100 Percentage
With temperature indication	✗		
With temperature limit	✓		
With circulation connection	✗		
With tap/mixer	✗		
With pressure reducing valve	✗		
With thermometer	✗		
With cleaning opening	✗		
Protective anode	✗		

Created on: 18/10/2024

PRODUCT DATASHEET

Cold tap water connection	External thread
Nominal diameter cold tap water	1/2 inch (15)
Hot tap water connection	External thread
Nominal diameter hot tap water	1/2 inch (15)
Circulation pipe connection	External thread
Nominal diameter circulation pipe	1/2 inch (15)
Connection, drainage connection	External thread
Nominal diameter drain connection	1/2 inch (15)
Degree of protection (IP)	IP24
Capacity profile	XXS
Energy efficiency class	A

Created on: 18/10/2024