

PRODUCT DATASHEET

Type: eTRACE-25-PRO
Art. Nr.: 41245



9120105414012

Short description

Self-regulating heating tape for pipes/gutters, 25W/m



*** Image missing:
/Data/Environments/000039/Attachment/Bijlage/PRD/Product/CHR/DE/etherma-db-41245-de.pdf ***

Product Description

The eTRACE-25-PRO self-regulating heating tape is suitable for temperatures up to 80 °C and can be used both as pipe trace heating and gutter heating. They are suitable for use in both domestic and industrial applications. The supply conductors are nickel-plated copper. All heating tapes are moisture-proof and UV-resistant. The right prerequisite for a long service life and absolute reliability. As self-regulating heating tapes, they can simply be cut to the required length and used immediately. Also suitable for plastic gutters in the gutter heating sector. As pipe trace heating, primarily as frost protection or for maintaining a constant temperature on pipes and containers. Nominal output 25 W/m at 10 °C in air, max. ambient temperature: 80 °C switched off and 65 °C switched on, min. installation temperature: -50 °C, min. bending radius: 25 mm, test mark: NEMKO, CE compliant.

ETIM characteristics

Cable type	Dual core	Nominal voltage	230 Volt
Constant power	✗	Max. hold temperature	65 Degrees celsius
Self-limiting	✓	Heating capacity	25 Watt per metre
Screening	Foil	Diameter	0 Millimetre
Material screening	CuNi	Height	5.8 Millimetre
Surface treatment screening	None	Width	12.5 Millimetre
Colour	Black	Length	1 Metre
Application	Gutter/roof		

Created on: 09/10/2024