

FICHE TECHNIQUE DU PRODUIT

Type: Stapaflex-FPR
Art. Nr.: 30011



Brève description

Tuyau d'installation Stapaflex asphalte DN 20



Description du produit

Tuyau d'installation blindé pour la pose de capteurs et de lignes de raccordement dans les surfaces en asphalte. Le tuyau résiste aux températures élevées lors de l'application de chaussées en asphalte.

Caractéristiques de l'ETIM

Material	Aluminium	Inner diameter	16 Millimetre
Material quality	Other	Outer diameter	20 Millimetre
Surface protection	Untreated	Operating temperature	220 220 Degrees celsius
Quality of surface coating	Other		
Surface polished	✗		
Surface brushed	✗		
Model	Pliable corrugated		
Connection 1	Other		
Connection 2	Other		
Colour	Grey		
Flush-mounted installation	✓		
Surface mounting	✗		
Suitable for concrete installation	✓		
Machine and systems installation	✓		
Suitable for underfloor installation (bitumen, hot asphalt)	✓		
Suitable for underfloor installation (screed)	✓		
Suitable for outdoor installation	✓		
Suitable for installation on wood	✓		
Suitable for hollow wall installation	✓		
Suitable for underground installation	✓		
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)		

Créé le: 09/10/2024