

FICHE TECHNIQUE DU PRODUIT

Type: KB-200
Art. Nr.: 34696



Brève description

Cassette pour convecteur mural à connexion fixe CP/CL



Description du produit

Cassette de connexion fixe pour raccordement facile des convecteurs CP et CL.

Caractéristiques de l'ETIM

Mounting method	Surface mounted	Number of connection clamps	2
Shape	Rectangular	Max. conductor cross section	1,5 Square millimetre
Extension possible	✓	Length	120 Millimetre
Type of inlet	Cable	Width	100 Millimetre
Material	Plastic	Depth	25 Millimetre
Halogen free	✓	Material plate thickness cabinet	2 Millimetre
Surface protection	Untreated	Number of inlets	1
Colour	White	RAL-number	9001
Degree of protection (IP)	IP24	Rated insulation voltage Ui	0 Volt
Degree of protection (NEMA)	Other	Nominal voltage	230 Volt
With cover	✓	Operating temperature	5 30 Degrees celsius
Cover attachment	Screwed	Rated current	16 Ampere
With transparent cover	✗		
Sealable	✗		
Circuit integrity	None		
Impact strength	Other		
Connection type	Other		
Explosion-tested version	✗		
For Ex-zone gas	None		
For Ex-zone dust	None		
Compliant with BS 6220	✗		
Maintenance free in accordance with BS 5733	✗		

Créé le: 09/10/2024