

FICHE TECHNIQUE DU PRODUIT

Type: ET-3356-50
Art. Nr.: 40788



9120061399408

Brève description

Capteur d'humidité et de température pour ET-9300 & -9200F câble 50m



Description du produit

L'ET-3356-

50 est un capteur de sol pour la mesure combinée des valeurs de température et d'humidité dans des espaces ouverts sur lesquels on peut conduire ou marcher. Il a une conception en laiton robuste et est entièrement encapsulé. Grâce à sa très faible hauteur hors tout, il est particulièrement adapté aux escaliers, terrasses, etc. Le câble de raccordement peut être conduit soit vers le bas, soit sur le côté. Y compris câble de raccordement 50 m, diamètre 68 mm, H 31 mm (câble sur le côté) ou 65 mm (câble descendant), capacité de charge 20 kN, plage de température -30 ° C à ° C, mesure d'humidité -20 ° C à ° C.

Caractéristiques de l'ETIM

| | | | |
|--|---------|--|-------------------------------|
| Scope of application | Outside | Cable length | 50 Metre |
| With mounting material | ✘ | Sensor length | 0 Millimetre |
| Suitable for wall mounting | ✘ | Insert length | 0 Millimetre |
| Suitable for ceiling mounting | ✘ | Diameter sensor element | 0 Millimetre |
| Suitable for duct mounting | ✘ | Number of measuring points | 1 |
| Suitable for tube mounting | ✘ | CO2 measuring range | 0 0 parts per million |
| Suitable for air | ✓ | VOC measuring range | 0 0 parts per million |
| Suitable for liquids | ✓ | Temperature measuring range | 75 Degrees celsius 75 |
| Suitable for gases | ✘ | Measuring range relative air humidity | 0 0 Percentage |
| With housing | ✓ | Measuring range absolute air humidity | 0 0 Gram per cubic metre |
| Cover attachment | Other | Enthalpy measuring range | 0 0 Kilojoule per kilogram |
| Sensor element inside housing | ✓ | Dewpoint measuring range | 0 0 Percentage |
| Sensor element outside housing | ✘ | Particulate matter measuring range (PM) | 0 0 Microgram per cubic metre |
| Fixed cable to sensor | ✓ | Number of measuring ranges | 1 |
| Material element | Other | Tolerance | 5 Percentage |
| Technology | Other | Rated supply voltage AC | 0 0 Volt |
| Active temperature measurement | ✓ | Rated supply voltage DC | 12 Volt 12 |
| Passive temperature measurement | ✘ | Number of output signals | 1 |
| Average temperature measuring | ✘ | Number of output ranges 0 V ... 5 V | 0 |
| Measurement of CO2 | ✘ | Number of output ranges 0 V ... 10 V | 0 |

Créé le: 09/10/2024

FICHE TECHNIQUE DU PRODUIT

| | | | |
|---|------------|--|---------------------------|
| Measurement of VOC | ✗ | Number of output ranges 2 V ... 10 V | 0 |
| Measurement of relative air humidity | ✓ | Number of output ranges 0 mA ... 20 mA | 0 |
| Measurement of absolute air humidity | ✗ | Number of output ranges 4 mA ... 20 mA | 0 |
| Enthalpy measurement | ✗ | Scope of application, flow speed medium | 0 0 Metre per second |
| Measurement of dewpoint | ✗ | Max. ambient humidity (non-condensing) | 10 Percentage 0 |
| Particulate matter measurement (PM) | ✗ | Ambient temperature | 75 Degrees celsius 75 |
| Offset setting possible | ✗ | Housing height | 35 Millimetre |
| Trend representation | ✗ | Housing width | 70 Millimetre |
| Error registration possible | ✗ | Housing depth | 70 Millimetre |
| Sensor type | PTC | | |
| Potentiometer with adjustment knob | ✗ | | |
| Supporting protocol for BACnet | ✗ | | |
| Supporting protocol for Modbus | ✗ | | |
| Supporting protocol for MP (multi point) | ✗ | | |
| Supporting protocol for KNX | ✗ | | |
| LoRa technology | ✗ | | |
| NFC (Near Field Communication) | ✗ | | |
| Bluetooth | ✗ | | |
| Wi-Fi-compatible | ✗ | | |
| Standby push button | ✗ | | |
| Wireless | ✗ | | |
| With display | ✗ | | |
| Type of display | Other | | |
| Type of power supply | Power cord | | |
| Type of electric connection | Other | | |
| With reverse polarity protection | ✗ | | |
| Explosion-proof | ✗ | | |
| Degree of protection (IP) | IP67 | | |
| Housing colour | Other | | |
| UV resistant | ✓ | | |
| Compatible with Apple HomeKit | ✗ | | |
| Compatible with Google Assistant | ✗ | | |
| Compatible with Amazon Alexa | ✗ | | |
| IFTTT support available | ✗ | | |

Cr  e le: 09/10/2024