

FICHE TECHNIQUE DU PRODUIT

Type: ET-AQUA-WHL-24
Art. Nr.: 41110



9120105411974

Brève description

Chauffe-eau instantané entièrement électronique avec affichage 24kW

**Description du produit**

L'AQUA WHL est un chauffe-eau instantané entièrement électronique avec écran LCD. Il convient parfaitement pour la préparation d'eau chaude dans la salle de bains. Un débit d'eau supérieur à 2,5 l/min provoque automatiquement la mise en marche du chauffage du chauffe-eau instantané. Le circuit de commande sélectionne la puissance de chauffage appropriée du chauffe-eau instantané en fonction du prélèvement d'eau, de la température souhaitée de l'eau et de la température de départ de l'eau. Au moyen d'un simple bouton de réglage, la température d'entrée et de sortie, le débit et la puissance peuvent être sélectionnés avec précision au degré près. Puissance : jusqu'à 15 ou 24 kW, Température : 30-60 °C, Pression de l'eau : 0,1-1,0 bar, pour montage mural, Couleur : blanc, Type de protection : IP 25, Classe d'efficacité énergétique : A, Raccordement d'eau : Gz 1/2", 40 °C.

Caractéristiques de l'ETIM

Material pressure tank	Plastic	Nominal content	0 Litre
Suitable for KNX	✗	Max. operating pressure	10 Bar
Operation	Manual	Nominal power	24 Kilowatt
Temperature indication	None	Nominal voltage 1	400 Volt
With display	✗	Nominal voltage 2	400 Volt
Mounting method	Over sink/under sink	Connected load	17/24 Kilowatt
Power control	4 steps	Outer pipe diameter cold tap water	12,7 Millimetre
Heating system	Tube heating element	Outer pipe diameter hot tap water	12,7 Millimetre
Safety breaker	Electronic	Height	440 Millimetre
Degree of protection (IP)	IP25	Width	245 Millimetre
Cold tap water connection	Internal thread	Depth	126 Millimetre
Nominal diameter cold tap water	1/2 inch (15)	Weight	4,85 Kilogram
Hot tap water connection	Internal thread		
Nominal diameter hot tap water	1/2 inch (15)		
Suitable for plastic tube	✓		
Suitable for preheated water	✓		
Type of regulation	Electronic		
With tap/mixer	✗		
Energy efficiency class according to 812/2013/EU	A		

Créé le: 09/10/2024