

FICHE TECHNIQUE DU PRODUIT

Type: SET-eFLOOR-LM-BASIC-1600
Art. Nr.: 41275



Brève description

Kit Laminotherm, avec thermostat eBASIC, 8m², 960W



Description du produit

Le kit eFLOOR LM BASIC se compose d'une natte chauffante dipôle Laminotherm, du thermostat encastrable intelligent eTWIST BASIC, ainsi qu'e d'un tube de protection du capteur FSH et d'un tuyau d'installation de 2,5 mètres et 12 mm de diamètre seulement. La natte chauffante Laminotherm de 120 W/m² impressionne par sa facilité d'installation et un câble de chauffage dipôle sans champ magnétique. L'eTWIST BASIC, doté d'un design intemporel, est un thermostat encastrable disposant d'un bouton de réglage et d'une application. Le réglage s'effectue à l'aide du bouton ou depuis un smartphone ou une tablette par Bluetooth via l'application gratuite eControl. Tension natte chauffante 230 V.

Caractéristiques de l'ETIM

Model	Other	Connection voltage	230 23 Volt 0
With support mat	×	Connected load	960 96 Watt 0
Fixation thermal conductor	Glued	Power	120 Watt per square metre
Self-adhesive	×	Heating conductor load	12 Watt per metre
Suitable for damp space	✓	Resistance	55 Ohm
Suitable as outdoor surface heating	×	Number of cold conductors	1
Suitable as roof surface heating	×	Length of cold conductors	5000 Millimetre
With controller	✓	Surface	8 Square metre
With room temperature controller	✓	Length	16000 Millimetre
With floor temperature sensor	✓	Width	500 Millimetre
		Thickness	3,3 Millimetre

Créé le: 09/10/2024