

Eaton 216727

Catalog Number: 216727

Eaton Moeller® series M22 Mushroom actuator, RMQ-Titan, Mushroom, momentary, Mushroom black, White, inscribed, Bezel: black



General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Mushroom actuator	216727
	Model Code
	M22S-DP-W-X1
EAN	Product Length/Depth
4015082167271	37 mm
Product Height	Product Width
43 mm	37 mm
Product Weight	Certifications
0.016 kg	NOM
	UL Listed
	CSA-C22.2 No. 14-05
	UL File No.: E29184
	CSA-C22.2 No. 94-91
	UL Category Control No.: NKCR
	IEC/EN 60947
	UL
	VDE 0660
	CSA Class No.: 3211-03
	IEC/EN 60947-5
	CE
	CSA
	CSA File No.: 012528
	UL 508
	DNV
	GL
	LR

Product specifications

Type

Mushroom-headed pushbutton

Actuator color

White

Actuator function

Spring-return

Momentary

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

Resources

Catalogs

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

Declarations of conformity

[DA-DC-00004135.pdf](#)

[DA-DC-00004157.pdf](#)

Drawings

[eaton-operating-m22-mushroom-actuator-dimensions-002.eps](#)

[eaton-operating-m22-mushroom-actuator-dimensions.eps](#)

[eaton-general-m22-standards.eps](#)

[eaton-general-m22-symbol.eps](#)

[eaton-operating-button-symbol-005.eps](#)

[116C090](#)

[eaton-general-approval-m22-symbol.eps](#)

eCAD model

[ETN.216727.edz](#)

Installation instructions

[IL04716002Z](#)

Installation videos

[RMQ Flat Design](#)

mCAD model

[DA-CS-pilzdrucktaste](#)

[DA-CD-pilzdrucktaste](#)

Multimedia

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

[RMQ small E-Stop emergency-stop button](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

Sales notes

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Front ring

Operating frequency

3600 Operations/h

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT

With SWD-RMQ connections

Yes

Actuating force

5 N

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

Specifications and datasheets

Eaton Specification Sheet - 216727

System overview

Pilot devices - selection aid

80 °C

Ambient storage temperature - min

40 °C

Diameter cap

36.5 mm

Equipment heat dissipation, current-dependent P_{vid}

0 W

Force for positive opening - min

0 N

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Opening diameter

22.5 mm

Opening height

0 mm

Rated operational current for specified heat dissipation (I_n)

0 A

Bezel color

Black

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal

shock 11 ms

Bezel material

Plastic

Design

Mushroom-shaped

Classical

Mounting position

As required

Degree of protection

IP67/IP69K

NEMA 4X, 13

Inscription

Inscribed

Front element type

Flat

Lens type

Round

Lifespan, mechanical

5,000,000 Operations

Static heat dissipation, non-current-dependent Pvs

0 W

Width opening

0 mm

Product category

RMQ-Titan

Size

Front dimensions: 22 x 22 mm

Supply voltage lamp

0 V

Unlocking method

None



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia