Eaton BK/SC-25

Catalog Number: BK/SC-25

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 25 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 10 kAIC at 300 Vdc, 100 kAIC at 480 Vac, Bulk, 480 V, 300 Vdc

General specifications



Eaton Bussmann series SC fuse

UPC

051712750134

Product Length/Depth

0.41 in

Product Width

0.41 in

Warranty

Not Applicable

Catalog Notes

Bulk

Catalog Number

BK/SC-25

EAN

5027590408325

Product Height

1.62 in

Product Weight

0.18 lb

Compliances

Not Applicable

RoHS Compliant



Electrical rating

Amperage Rating

25 A

Interrupt rating

10 kAIC at 300 Vdc 100 kAIC at 480 Vac

Response time

12 sec at 200%

Voltage rating

480 Vac, 300 Vdc

Physical details

Packaging type

Standard

Bulk

General information

Class

Class G

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Rejection style

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

BK/SC-25~BK-SC-25~BUSS SC FUSE CLASS G

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - BK/SC-25

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.













