

Eaton 216638

Catalog Number: 216638

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Extended, momentary, White, Blank, Bezel: titanium



General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Pushbutton	216638
Model Code	EAN
M22-DH-W	4015082166380
Product Length/Depth	Product Height
30 mm	35 mm
Product Width	Product Weight
30 mm	0.012 kg

Certifications

CSA
UL
IEC/EN 60947-5
VDE 0660
CSA Class No.: 3211-03
UL 508
CSA File No.: 012528
CSA-C22.2 No. 94-91
UL File No.: E29184
CE
CSA-C22.2 No. 14-05
IEC/EN 60947
UL Category Control No.: NKCR
DNV
GL
LR

Product specifications

Type

Pushbutton actuator

Actuator color

White

Actuator function

Momentary

Spring-return

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

Resources

Catalogs

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

Declarations of conformity

[DA-DC-00004135.pdf](#)

[DA-DC-00004157.pdf](#)

Drawings

[eaton-operating-pushbutton-m22-dimensions.eps](#)

[eaton-operating-pushbutton-m22-dimensions-005.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

[eaton-operating-samrtwire-m22-3d-drawing-002.eps](#)

[eaton-general-m22-symbol.eps](#)

[eaton-operating-button-symbol-013.eps](#)

[eaton-general-m22-standards.eps](#)

eCAD model

[ETN.216638.edz](#)

Installation instructions

[IL04716002Z](#)

Installation videos

[RMQ Flat Design](#)

mCAD model

[DA-CS-drucktaste_hoch](#)

[DA-CD-drucktaste_hoch](#)

Multimedia

[RMQ small E-Stop emergency-stop button](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

Sales notes

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Front ring

Operating frequency

3600 Operations/h

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Connection to SmartWire-DT

Yes

With SWD-RMQ connections

Actuating force

5 N

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

Specifications and datasheets

Eaton Specification Sheet - 216638

System overview

Pilot devices - selection aid

80 °C

Ambient storage temperature - min

40 °C

Equipment heat dissipation, current-dependent Pvid

0 W

Force for positive opening - min

0 N

Heat dissipation capacity Pdis

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Number of command positions

1

Opening diameter

22.5 mm

Opening height

0 mm

Rated operational current for specified heat dissipation (In)

0 A

Bezel color

Titanium

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal

shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

Bezel material

Plastic

Design

Extended

Classical

Mounting position

As required

Degree of protection

NEMA 3R

NEMA 4X

IP66

NEMA 12

NEMA 13

IP67

IP69K

Degree of protection (front side)

IP67/IP69K

NEMA 4X

Inscription

Blank

Front element type

High

Lens type

Round

Lifespan, mechanical

5,000,000 Operations

Static heat dissipation, non-current-dependent Pvs

0 W

Width opening

0 mm

Product category

RMQ-Titan

Size

Front dimensions: 22 x 22 mm



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia