

Eaton 170M6059

Catalog Number: 170M6059

Fuse-link, high speed, 550 A, AC 690 V, DIN 3, 76 x 90 x 109 mm, aR, DIN, IEC, single indicator

General specifications



Product Name

Eaton Bussmann series high speed square body fuse

Catalog Number

170M6059

UPC

051712262668

EAN

5027590289818

Product Length/Depth

168 mm

Product Height

76 mm

Product Width

95 mm

Product Weight

1384 g

Warranty

Not Applicable

Compliances

CE Marked
RoHS Compliant

Certifications

IEC Rated
UL Recognized

Product specifications

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

550 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

3

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

135000 at 660 V

Watt losses

100 W

Clearing loss

100

Resources

Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf](#)

Specifications and datasheets

[Eaton Specification Sheet - 170M6059](#)

Technical data sheets

[720014 DIN 43653 690V](#)

Fuse shape

Square body, slotted center bolted tags

Pre arc (I2T)

19500

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

3

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia