# Eaton RS2-11-C10

## Catalog Number: RS2-11-C10

Eaton RS-Titan non-contact door interlock safety switch, Magnetic Reed Switch, Polyamide enclosure, 300 mA max DC, 1 Normally Open and 1 Normally Closed, 300 mA at 24 Vdc, 33 Ft. (10m) Cable, < 10% accuracy, 33 Ft. (10m)

### General specifications



Product Name Catalog Number

Eaton RS-Titan non-contact door RS2-11-C10

interlock safety switch UPC

786685886367

Product Length/Depth Product Height

0.94 in 2 in

Product Width Product Weight

0.44 in 0.875 lb

Warranty Compliances

1 year CE Marked

Certifications Catalog Notes

UL Listed 0



### Product specifications

Туре

Mechanical Limit Switches

**Contact Rating** 

300 mA at 24 Vdc

Cable type

Polyvinyl Chloride (PVC)

Accuracy

< 10%

**Enclosure material** 

Polyamide

Cord length

396 ft

Connection

33 ft (10m) cable

Contact configuration

1 NO-1 NC

Switch type

Magnetic reed switch

Operating temperature - max

131 °F

Operating temperature - min

14 °F

Environmental rating

IP67, IP69K

Maximum DC current

300 mA

#### Resources

Specifications and datasheets

Eaton Specification Sheet - RS2-11-C10



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia