

# PRODUCT DATASHEET SMART+ ZB GardenPole 3P RGB + W

Smart+ Garden Pole Multicolor | Decorative light poles for outdoor use with Zigbee technology



#### Areas of application

- Gardens, balconies and other outdoor areas

#### Product benefits

- Easy to install and use
- Colorful garden lighting with smart and intelligent control options
- Uses multi color and cold or warm white light for most flexible lighting scenes
- The basic set is extendable with the extension set up to 11 poles
- Combines the functionality of general lighting and mood lighting

#### Product features

- Five-pole starter set easily expandable with the three-pole extension kit
- Garlands of lights with integrated wireless smart lighting function
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 2,000...6,500 K



- Protection class (pole): IP65
- Protection class (power supply): IP44
- Network protocol: ZigBee
- Lifetime: up to 20,000 h
- Controllable via compatible smart home system (gateway and app) or SMART+ Switch
- For full functionality, connection to a compatible smart home System (gateway and app) required

# TECHNICAL DATA

## Electrical data

| Nominal wattage        | 3.00 W              |
|------------------------|---------------------|
| Nominal voltage        | 220240 V            |
| Mains frequency        | 5060 Hz             |
| Nominal current        | 150.000 mA          |
| Power factor $\lambda$ | > 0.5               |
| Protection class       | П                   |
| Operating mode         | External LED driver |

#### Photometrical data

| Luminous flux                                  | 420 lm              |  |
|--|---------------------|--|
| Total luminous flux of contained light sources | 252 lm              |  |
| Luminous efficacy                              | 84 lm/W             |  |
| Color temperature                              | 2000 6500 K         |  |
| Light color (designation)                      | Tunable White / RGB |  |
| Color rendering index Ra                       | > 80                |  |
| Standard deviation of color matching           | 6 sdcm              |  |
| Flickering metric (Pst LM)                     | <1 %                |  |
| Stroboscope effect metric (SVM)                | <0.4                |  |
| Photobiological safety group acc. to EN62778   | RG0                 |  |
| Beam angle                                     | 160 °               |  |

# Dimensions & Weight

| Diameter       | 60.00 mm   |
|----------------|------------|
| Length         | 6000.00 mm |
| Width          | 60.00 mm   |
| Height         | 367.00 mm  |
| Product weight | 540.00 g   |

## Materials & Colors

| Product color                              | Grey     |
|--|----------|
| Housing color                              | Gray     |
| Body material                              | Aluminum |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C   |
| Mercury content                            | 0.0 mg   |

# **Application & Mounting**

| Ambient temperature range | -20+40 °C        |
|---------------------------|------------------|
| Type of connection        | Plug type C (EU) |
| Type of protection        | IP65             |
| Dimmable                  | Yes              |
| Mounting type             | Ground spike     |
| Mounting location         | Ground           |
| Application environment   | Outdoor          |
| LED module replaceable    | Not replaceable  |
| With light source         | Yes              |

# Lifespan

| Lifespan L70/B50 at 25 °C  | 20000 h |
|----------------------------|---------|
| Number of switching cycles | 10000   |

## Certificates & Standards

| Standards | CE |
|-----------|----|
|           |    |

# Additional product data

| Product remark  Reset settings to default by switching the product on for five seconds and off for five seconds and repeating this five times. | nds |
|--|-----|
|--|-----|

#### **EQUIPMENT / ACCESSORIES**

- Power supply included only in basic set
- Control via app requires LIGHTIFY system (app and gateway) or other compatible Smart home system

## DOWNLOAD DATA

|     | Documents and certificates | Document name                           |  |
|-----|----------------------------|---|--|
| PDF | User Instruction           | SMART ZB GARDENPOLE RGBW                |  |
| PDF | Declarations of conformity | CE Declaration SMART ZB GARDENPOLE RGBW |  |

# LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854043932 | Folding box<br>1             | 67 mm x 304 mm x 173 mm              | 836.00 g     | 3.52 dm <sup>3</sup> |
| 4099854043949 | Shipping box                 | 315 mm x 184 mm x 151 mm             | 1671.00 g    | 8.75 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.