

PRODUCT DATASHEET Panan Disc Single Gray DIM 3000K

PANAN® Disc Single | Mobile table luminaires with continuous dimming



Areas of application

- Where light is required but a socket is not available
- Whenever a cableless solution is preferred
- When flexible lighting is required
- Living areas
- Tables, Desks

Product benefits

- Can easily be moved to where light is needed thanks to battery operation
- Switching and stepless dimming via a touch sensitive sensor on the luminaire base
- Bendable luminaire neck for free orientation of light source

Product features

- Integrated rechargeable lithium battery which can be charged via USB cable
- Light color: Warm White
- Housing made of plastic, luminare neck made of silicone rubber
- Battery discharge time: up to 4 h



TECHNICAL DATA

Electrical data

| Nominal wattage | 5.00 W |
|------------------|---------|
| Nominal voltage | 5 V |
| Protection class | III |
| Operating mode | Battery |

Photometrical data

| Luminous flux | 220 lm |
|--|------------|
| Luminous efficacy | 44 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | ≤6 sdcm |
| Photobiological safety group acc. to EN62778 | RG0 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 105° |

Dimensions & Weight

| Length | 350.00 mm |
|----------------|-----------|
| Width | 170.00 mm |
| Height | 370.00 mm |
| Product weight | 435.00 g |



Materials & Colors

| Product color Gray |
|--------------------|
|--------------------|

| Housing color | Gray | |
|---------------------------------|---------------------------------------|--|
| Body material | Acrylonitrile butadiene styrene (ABS) | |
| Cover material | Plastic | |
| Light emitting surface material | Plastic | |
| Mercury content | 0.0 mg | |

Application & Mounting

| Ambient temperature range | 0+40 °C |
|------------------------------|-----------------|
| Temperature range at storage | -25+70 °C |
| Type of connection | USB |
| Type of protection | IP20 |
| Dimmable | Yes |
| Dimming range | 10100 % |
| Mounting type | Surface |
| Mounting location | Table |
| Application environment | Indoor |
| Adjustable | Yes |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
|----------------------------|-----------------------|
| Number of switching cycles | 100000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

| Type of Battery | Lithium ion |
|------------------------------|-------------|
| Battery size [GMS] | 18650 |
| Number of included batteries | 1 |
| Nominal voltage of battery | 3.7 V |
| Nominal capacity of battery | 2200 mAh |
| Battery charging time | 6 h |

Certificates & Standards

| Standards | CE / EAC |
|-----------|----------|
| | |

EQUIPMENT / ACCESSORIES

- USB cable, lenght: 1 m

DOWNLOAD DATA

| Documents and certificates Docu | | Document name |
|---------------------------------|----------------------------|-------------------|
| PDF | User Instruction | PANAN DISC SINGLE |
| PDF | Declarations of conformity | Table lamp PANAN |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075472754 | Folding box 1 | 176 mm x 176 mm x 366 mm | 542.00 g | 11.34 dm ³ |
| 4058075472761 | Shipping box 4 | 364 mm x 364 mm x 381 mm | 2587.00 g | 50.48 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.