

PRODUCT DATASHEET

FLASHLIGHT CAR MULTI-USE

FLASHLIGHT CAR MULTI-USE | Outdoor mobiles



Product benefits

- Dimmable: max 400 lm
- 2 hours of running at full brightness
- 3 hours to fully charge from empty-to-full
- Battery capacity: 1800 mA
- Type of protection: IP22

Product features

- Long, thin body for illuminating hard-to-reach areas
- Easy to operate with one hand
- Hook on top, magnetic base
- Soft touch housing
- Rotary brightness switch
- Hanging bracket

TECHNICAL DATA

Electrical data

Nominal wattage	5.00 W
Inrush current	1350 mA
Inrush current time T _{h50}	0.5 s
Operating mode	Battery

Photometrical data

Luminous flux	400 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Cool White
Color rendering index Ra	70

Dimensions & Weight

Length	408.00 mm
Width	33.00 mm
Height	30.00 mm
Product weight	155.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	ABS I TPR (Thermoplastic rubber)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	USB Type-C
Dimmable	No
Adjustable	No
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

Battery size [GMS]	Others
Battery charging time	3 h

Certificates & Standards

Standards	CE / UKCA
-----------	-----------

EQUIPMENT / ACCESSORIES

– USB C cable

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854175640	Folding box 1	50 mm x 38 mm x 413 mm	199.00 g	0.78 dm ³
4099854175657	Shipping box 24	440 mm x 253 mm x 240 mm	5298.00 g	26.72 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.