

PRODUCT DATASHEET

URB LTRN V 29W ASYM PS 830-840 IP66 BK

URBAN LANTERN ASYMMETRIC | Fitting pathway, bicycle path lighting applications



VALUE
CLASS

Areas of application

- Replacement for luminaires with mercury vapor or metal halide lamps
- Streets
- Residential installations
- Pedestrian zones
- Parks
- Public areas

Product benefits

- Highly versatile due to selectable CCT and power steps (Power Select - PS)
- Low flicker light thanks to special electronic control gear
- Energy savings thanks to system efficacy of up to 139 lm/W
- Bright, robust and durable
- 5 years guarantee

Product features

- Protection class: II
- Lifetime (L80/B10): up to 100,000 h (at 25 °C)
- Type of protection: IP66
- Impact resistance: IK10
- Asymmetric light distribution

TECHNICAL DATA

Electrical data

Nominal wattage	29 W / 25 W / 20 W / 15 W ¹⁾
Nominal voltage	220...250 V
Mains frequency	50...60 Hz
Nominal current	70 mA
Inrush current time T _{h50}	330 µs
Max. number of luminaires per miniature circuit breaker B16	8
Max. number of luminaires per miniature circuit breaker C16	13
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	Integrated LED driver

¹⁾ For possible options refer to lumen/power table image

Photometrical data


Luminous flux	3945 lm / 3400 lm / 2720 lm / 2040 lm ¹⁾
Luminous efficacy	136 lm/W ¹⁾
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	80
Standard deviation of color matching	5 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1

¹⁾ For possible options refer to lumen/power table image

URB LTRN V29/59W ASYMPS

Dimensions & Weight

Diameter	395.00 mm
Height	417.00 mm
Product weight	4155.00 g



URBAN LANTERN

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	750 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Temperature range at storage	-30...80 °C
Type of connection	Cable, 3-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Post top
Mounting location	Pole
Application environment	Outdoor
Adjustable	No
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L90/B10 at 25 °C	68000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA / EAC / ENEC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Added function	MULTI SELECT
----------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	URBAN LANTERN
	Addon Technical Information	URBAN LANTERN
	Legal information	URBAN LANTERN
	Declarations of conformity	CE Declaration URBAN LANTERN
	Declarations Of Conformity UKCA	UKCA Declaration URBAN LANTERN
	Certificates	ENEC Certificate URBAN LANTERN
	Certificates	CEE Eligibility Attestation RES-EC-104 FR
Photometric and lighting design files		Document name
	IES file (IES)	URBAN LANTERN V 29W ASYM PS 830 IP66 BK
	IES file (IES)	URBAN LANTERN V 29W ASYM PS 840 IP66 BK
	LDT file (Eulumdat)	URBAN LANTERN V 29W ASYM PS 830 IP66 BK
	LDC typ polar	URB LTRN V29/59W ASYMPS
Tender texts		Document name
	Tender documents	URBAN LANTERN ASYMMETRIC 29W ASYM PS 830 840 IP66 BK-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854246784	Shipping box 1	435 mm x 435 mm x 220 mm	4520.00 g	41.63 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.