


PRODUCT DATASHEET

Decor Circle 3XPendant PL 20W Click CCT Black

Decor Circle | Decorative luminaires made of acrylic and metal with LED



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

Product benefits

- High-quality look and feel
- Minimalistic design with elegant decorative lighting
- Different types of luminaires with the same design language maintain a consistent style at home
- Easy mounting
- Highly versatile due to selectable CCT

Product features

- Housing material: acrylic
- High-power LED



TECHNICAL DATA

Electrical data


Nominal wattage	20.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	95.000 mA
Inrush current	0.095 A
Inrush current time T _{h50}	186 µs
Max. number of luminaires per miniature circuit breaker B16	19
Max. number of luminaires per miniature circuit breaker C10	16
Max. number of luminaires per miniature circuit breaker C16	25
Power factor λ	> 0.90
Total harmonic distortion	80 %
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	1300 lm
Total luminous flux of contained light sources	2400 lm
Luminous efficacy	65 lm/W
Color temperature	3000 K / 4200 K / 6500 K
Reference control setting of contained light source (Kelvin)	3000 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdc _m
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG0

Dimensions & Weight

Length	280.00 mm
Width	200.00 mm
Height	1210.00 mm
Product weight	1120.00 g



DECOR CIRCLE 3XPEND PL 18W
CLICKCCT

Materials & Colors

Product color	Black
Housing color	Black
Body material	Polymethylmethacrylate (PMMA)
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Suspended
LED module replaceable	Not replaceable
With light source	Yes

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Product remark	Available from October 2024
----------------	-----------------------------

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	DECOR CIRCLE PEND PL CLICKCCT LEDV

Documents and certificates		Document name
	Legal information	DECOR DRUMS/CIRCLE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075838642	Folding box 1	257 mm x 257 mm x 318 mm	1450.00 g	21.00 dm³
4058075838659	Shipping box 4	535 mm x 270 mm x 660 mm	6999.00 g	95.34 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.