



Color: ■ gray

Physical data	
Width	3 mm / 0.118 inches
Height	23 mm / 0.906 inches
Depth	33.4 mm / 1.315 inches

Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.054 MJ
Weight	1.6 g

Environmental requirements	
Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data	
Product Group	9 (Std Chassis Mt Blocks)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 9.0	EC000886
ETIM 8.0	EC000886
PU (SPU)	200 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4017332143066
Customs tariff number	85389099990



Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 262-371	↓

Documentation			
Additional Information		Bid Text	
Technical Section	pdf 2246.92 KB	262-371	19.02.2019 xml 2.53 KB
	↓	262-371	17.08.2017 doc 23.00 KB
			↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 262-371	EPLAN Data Portal 262-371
↓	↓
	WSCAD Universe 262-371
	↓
	ZUKEN Portal 262-371
	↓

1 Compatible Products
1.1 Optional Accessories
1.1.1 Installation
1.1.1.1 Mounting accessories



Item No.: [209-120](#)
Mounting foot; can be snapped on terminal blocks with snap-in mounting foot; for mounting on relay-modules; 6.4 mm wide; gray