




Color: ■ blue



Dimensions in mm

Cable assembly WINSTA® MINI with strain relief

For signal and power transmission: The WINSTA® MINI cable assembly rated current 16 A. On PCBs, in control cabinets or for connecting lights – pluggable installation connectors from WAGO allow you to make connections according to an enormous variety of requirements in no time flat. For greater protection in electrical installations, the pluggable installation connector is equipped with mechanical protection against mismating. I coding in blue is used to mark WINSTA® MINI pluggable installation connectors, which are used above all in building automation for activating lighting. WINSTA® MINI satisfies the demand for miniaturisation. Our smallest pluggable connection system is primarily suited for lights, for example, since as a result of LED technology; due to complex systems, these offer significantly less space for the connection technology. According to the European CPR, the fire class of the cables used in construction is decisive for the safety of buildings, too. For houses with medium-level safety requirements, cable assemblies with fire class E are suitable.

Pluggable connections instead of screw connections – cable assemblies from WAGO

The cable assembly is provided with a plug and a free end. WINSTA® is the pluggable connection system that is ideally tailored to the strict requirements of electrical installation. It ensures fast, secure and, above all, error-free installation of components and cables. Enjoy the benefits of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with with marking from WAGO.

- protection against mismating eliminates errors
- consistent IP40 protection
- with I coding for controlling light (DALI standard)
- custom-engineered solutions
- convenient installation and commissioning

| Notes |                                                               |
|-------|---------------------------------------------------------------|
| Note  | Cables with a different fire class can be found in the eShop. |

| Electrical data      |       |                |     |    | General information                             |  |
|----------------------|-------|----------------|-----|----|-------------------------------------------------|--|
| Ratings per          |       | IEC/EN 60664-1 |     |    | Note on contact resistance                      |  |
| Overvoltage category |       | III            | III | II | approx. 1 mΩ of contact resistance              |  |
| Pollution degree     |       | 3              | 2   | 2  | approx. 0.25 mΩ contact transition plug/ socket |  |
| Nominal voltage      | 250 V | -              | -   | -  |                                                 |  |
| Rated surge voltage  | 4 kV  | -              | -   | -  |                                                 |  |
| Rated current        | 16 A  | -              | -   | -  |                                                 |  |



| Connection data            |                           |                                 |                    |
|----------------------------|---------------------------|---------------------------------|--------------------|
| Total number of potentials | 2                         | Connection 1                    |                    |
| Conductor preparation      | ultrasonically tip-bonded | Strip length                    | 9 mm / 0.35 inches |
|                            |                           | Pole number                     | 2                  |
|                            |                           | Wire cross-section              | 1.5 mm²            |
|                            |                           | Strip length (outer insulation) | 32 mm              |
|                            |                           | Connection type                 | Plug - free end    |

| Physical data |  |                        |  |
|---------------|--|------------------------|--|
| Pin spacing   |  | 4.4 mm / 0.173 inches  |  |
| Width         |  | 15.6 mm / 0.614 inches |  |
| Height        |  | 13.2 mm / 0.52 inches  |  |
| Total length  |  | 5 m                    |  |

| Mechanical data                         |  |                                                               |  |
|-----------------------------------------|--|---------------------------------------------------------------|--|
| Use                                     |  | DALI, Lighting Management                                     |  |
| Coding                                  |  | I                                                             |  |
| Variable coding                         |  | No                                                            |  |
| Marking                                 |  | + -                                                           |  |
| Potential marking                       |  | + -                                                           |  |
| Mating force of a plug-in connection    |  | approx. 20 ... 70 N (depending on pole number)                |  |
| Retention force of a plug-in connection |  | when locked: > 80N                                            |  |
| Unmating force of a plug-in connection  |  | when unlocked: approx. 20 ... 70 N (depending on pole number) |  |
| Number of mating cycles                 |  | 200, without resistive load                                   |  |
| Connection type                         |  | Plug - free end                                               |  |
| Type of pre-assembled cable             |  | Connecting cable                                              |  |
| Cable type                              |  | H05VV-F 2x1.5                                                 |  |
| Protection type                         |  | IP20; IP40 when mated                                         |  |

| Plug-in connection            |  |                                                                                                                                                                                                                                                                                                                  |  |
|-------------------------------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Mismating protection          |  | Yes                                                                                                                                                                                                                                                                                                              |  |
| Note on mismating protection  |  | All WINSTA® components are 100% protected against mismating when:<br>a.) plugging different numbers of poles<br>b.) plugging while rotated 180<br>c.) plugging while laterally staggered<br>d.) plugging one pole                                                                                                |  |
| Locking lever                 |  | Can be retrofitted                                                                                                                                                                                                                                                                                               |  |
| Locking of plug-in connection |  | Locking lever                                                                                                                                                                                                                                                                                                    |  |
| Note on locking system        |  | All connectors for mounted installations (snap-in versions for lighting fixtures or devices, all types of PCB and distribution connectors) are factory-equipped with locking levers to ensure plugs and sockets are securely locked. Additional locking levers are only required for flying leads (plug/socket). |  |

| Material data                      |  |                                                                          |  |
|------------------------------------|--|--------------------------------------------------------------------------|--|
| Note (material data)               |  | <a href="#">Information on material specifications can be found here</a> |  |
| Color                              |  | blue                                                                     |  |
| Insulation material (main housing) |  | Polyamide (PA66)                                                         |  |
| Fire class per EN 50575            |  | E <sub>ca</sub>                                                          |  |
| Contact material                   |  | Copper or copper alloy; surface-treated                                  |  |
| Contact Plating                    |  | Tin                                                                      |  |
| Fire load                          |  | 149.664 MJ                                                               |  |
| Connector color                    |  | blue                                                                     |  |
| Strain relief color                |  | white                                                                    |  |



| Material data                    |            |
|----------------------------------|------------|
| Sheathed cable color             | white      |
| Printing color of sheathed cable | black      |
| Halogen-free                     | No         |
| Silicon-free                     | Yes        |
| Sheath material                  | PVC        |
| Rubber cable                     | No         |
| Weight                           | 414.3 g    |
| Copper weight of the pipe        | 0.029 kg/m |

| Environmental requirements               |                                                                                                       |
|------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Processing temperature                   | -5 ... +40 °C                                                                                         |
| Continuous operating temperature         | -35 ... +85 °C                                                                                        |
| Note on continuous operating temperature | Cable for temperatures ≤ 70 °C (including halogen-free)<br>Insulating parts for temperatures ≤ 105 °C |

| Commercial data       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-44-06-04   |
| eCl@ss 9.0            | 27-44-06-04   |
| ETIM 9.0              | EC002587      |
| ETIM 8.0              | EC002587      |
| PU (SPU)              | 1 pcs         |
| Packaging type        | unpacked      |
| Country of origin     | PL            |
| GTIN                  | 4055143362672 |
| Customs tariff number | 85444290900   |

| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

| Approvals / Certificates                                |          |                                                            |
|---------------------------------------------------------|----------|------------------------------------------------------------|
| General approvals                                       |          | Declarations of conformity and manufacturer's declarations |
| <div><div>CCA</div><div>KEMA<br/>KEUR</div></div>       |          |                                                            |
| Approval                                                | Standard | Certificate Name                                           |
| CCA<br>DEKRA Certification B.V.                         | EN 61535 | NTR NL-7971                                                |
| KEMA/KEUR<br>DEKRA Certification B.V.                   | EN 61535 | 71-123232                                                  |
| Approval                                                | Standard | Certificate Name                                           |
| EU-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                                                          |
| UK-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                                                          |



Downloads

Environmental Product Compliance

|                                  |  |  |   |
|----------------------------------|--|--|---|
| Compliance Search                |  |  |   |
| Environmental Product Compliance |  |  | ↓ |
| 891-8982/206-502                 |  |  |   |

Documentation

|                  |            |                 |   |
|------------------|------------|-----------------|---|
| Bid Text         |            |                 |   |
| 891-8982/206-502 | 19.02.2019 | xml<br>3.05 KB  | ↓ |
| 891-8982/206-502 | 24.11.2014 | doc<br>24.50 KB | ↓ |

CAD/CAE-Data

|                  |  |  |   |
|------------------|--|--|---|
| CAE data         |  |  |   |
| WSCAD Universe   |  |  | ↓ |
| 891-8982/206-502 |  |  |   |

1 Compatible Products

1.1 Required Accessories

1.1.1 Locking system

1.1.1.1 Locking system



[Item No.: 890-111](#)  
Locking lever; for flying leads; for tool operation; black



[Item No.: 890-131](#)  
Locking lever; for flying leads; for tool operation; white



[Item No.: 890-101](#)  
Locking lever; for manual operation; black



[Item No.: 890-121](#)  
Locking lever; for manual operation; white

1.2 Optional Accessories

1.2.1 Cover

1.2.1.1 Cover



[Item No.: 897-2001](#)  
Protective cap; Type1; for sockets and plugs; PVC; red



1.2.2 Installation

1.2.2.1 Mounting accessories



[Item No.: 890-310](#)  
Mounting carrier; 2- to 5-pole; for flying leads; black

[Item No.: 890-311](#)  
Mounting carrier; 2- to 5-pole; for flying leads; white