





Color:  white



Dimensions in mm

Cable assembly WINSTA® MINI rated current 13 A

The WINSTA® MINI cable assembly rated current 13 A supports rapid, correct installation. Whether on PCBs, in control cabinets or for connecting lights – pluggable installation connectors from WAGO allow you to make connections according to an enormous variety of requirements in no time flat. For greater protection in electrical installations, the pluggable installation connector is provided with mechanical protection against mismating. Thanks to the color coding and mechanical A coding of WINSTA® MINI pluggable installation connectors, you can clearly distinguish different circuits. Thanks to its particularly compact dimensions, our WINSTA® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is specifically suitable in very restricted spaces, i.e., for installations when very little room is available. According to the European CPR, the fire class of the cables used for construction is essential for the safety of buildings, too. For buildings with average safety requirements, cable assemblies with fire class E are suitable.

Fast, error-free assembly thanks to cable assemblies from WAGO

A plug and a free end are provided. WINSTA® is the pluggable connection system that is optimally tailored to the strict requirements of electrical installation. It allows error-free installation of cables and components, quickly and reliably. Now you can also lower installation expenses without compromising quality and safety: with marking reduces the need for servicing and prevents unnecessary downtime.

- protection against mismating eliminates errors
- easy tool-free operation, a wide range of coding options
- suitable for any application
- ready to install and use immediately
- rapid, structured electrical installation

| Notes |                                                               |
|-------|---------------------------------------------------------------|
| Note  | Cables with a different fire class can be found in the eShop. |

| Electrical data      |       |                |    | General information                             |  |
|----------------------|-------|----------------|----|-------------------------------------------------|--|
| Ratings per          |       | IEC/EN 60664-1 |    | Note on contact resistance                      |  |
| Overvoltage category | III   | III            | II | approx. 1 mΩ of contact resistance              |  |
| Pollution degree     | 3     | 2              | 2  | approx. 0.25 mΩ contact transition plug/ socket |  |
| Nominal voltage      | 400 V | -              | -  |                                                 |  |
| Rated surge voltage  | 6 kV  | -              | -  |                                                 |  |
| Rated current        | 13 A  | -              | -  |                                                 |  |

| Connection data            |                           |                                 |                    |
|----------------------------|---------------------------|---------------------------------|--------------------|
| Total number of potentials | 5                         | Connection 1                    |                    |
| Conductor preparation      | ultrasonically tip-bonded | Strip length                    | 9 mm / 0.35 inches |
|                            |                           | Pole number                     | 5                  |
|                            |                           | Wire cross-section              | 1.5 mm²            |
|                            |                           | Strip length (outer insulation) | 45 mm              |
|                            |                           | Connection type                 | Plug - free end    |

| Physical data |  |                        |  |
|---------------|--|------------------------|--|
| Pin spacing   |  | 4.4 mm / 0.173 inches  |  |
| Width         |  | 26.7 mm / 1.051 inches |  |
| Height        |  | 15.8 mm / 0.622 inches |  |
| Total length  |  | 5 m                    |  |

| Mechanical data                         |  |                                                               |  |
|-----------------------------------------|--|---------------------------------------------------------------|--|
| Use                                     |  | General mains applications                                    |  |
| Coding                                  |  | A                                                             |  |
| Variable coding                         |  | No                                                            |  |
| Marking                                 |  | N ⊕ 1 2 3                                                     |  |
| Potential marking                       |  | N ⊕ 1 2 3                                                     |  |
| Mating force of a plug-in connection    |  | approx. 20 ... 70 N (depending on pole number)                |  |
| Retention force of a plug-in connection |  | when locked: > 80N                                            |  |
| Unmating force of a plug-in connection  |  | when unlocked: approx. 20 ... 70 N (depending on pole number) |  |
| Number of mating cycles                 |  | 200, without resistive load                                   |  |
| Connection type                         |  | Plug - free end                                               |  |
| Type of pre-assembled cable             |  | Connecting cable                                              |  |
| Cable type                              |  | H05VV-F 5G1.5                                                 |  |
| Protection type                         |  | IP20; IP40 when mated                                         |  |

| Plug-in connection            |  |                                                                                                                                                                                                                                                                                                                  |  |
|-------------------------------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Mismating protection          |  | Yes                                                                                                                                                                                                                                                                                                              |  |
| Note on mismating protection  |  | All <i>WINSTA</i> ® components are 100% protected against mismating when:<br>a.) plugging different numbers of poles<br>b.) plugging while rotated 180<br>c.) plugging while laterally staggered<br>d.) plugging one pole                                                                                        |  |
| Locking lever                 |  | Can be retrofitted                                                                                                                                                                                                                                                                                               |  |
| Locking of plug-in connection |  | Locking lever                                                                                                                                                                                                                                                                                                    |  |
| Note on locking system        |  | All connectors for mounted installations (snap-in versions for lighting fixtures or devices, all types of PCB and distribution connectors) are factory-equipped with locking levers to ensure plugs and sockets are securely locked. Additional locking levers are only required for flying leads (plug/socket). |  |

| Material data                      |  |                                                                          |  |
|------------------------------------|--|--------------------------------------------------------------------------|--|
| Note (material data)               |  | <a href="#">Information on material specifications can be found here</a> |  |
| Color                              |  | white                                                                    |  |
| Insulation material (main housing) |  | Polyamide (PA66)                                                         |  |
| Fire class per EN 50575            |  | E <sub>ca</sub>                                                          |  |
| Contact material                   |  | Copper or copper alloy; surface-treated                                  |  |
| Contact Plating                    |  | Tin                                                                      |  |
| Fire load                          |  | 149.992 MJ                                                               |  |
| Connector color                    |  | white                                                                    |  |
| Strain relief color                |  | white                                                                    |  |



| Material data                    |            |
|----------------------------------|------------|
| Sheathed cable color             | white      |
| Printing color of sheathed cable | black      |
| Halogen-free                     | No         |
| Silicon-free                     | Yes        |
| Sheath material                  | PVC        |
| Rubber cable                     | No         |
| Weight                           | 785.2 g    |
| Copper weight of the pipe        | 0.072 kg/m |

| Environmental requirements               |                                                                                                       |
|------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Processing temperature                   | -5 ... +40 °C                                                                                         |
| Continuous operating temperature         | -35 ... +85 °C                                                                                        |
| Note on continuous operating temperature | Cable for temperatures ≤ 70 °C (including halogen-free)<br>Insulating parts for temperatures ≤ 105 °C |

| Commercial data       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-44-06-04   |
| eCl@ss 9.0            | 27-44-06-04   |
| ETIM 9.0              | EC002587      |
| ETIM 8.0              | EC002587      |
| PU (SPU)              | 1 pcs         |
| Packaging type        | unpacked      |
| Country of origin     | PL            |
| GTIN                  | 4055143398954 |
| Customs tariff number | 85444290900   |

| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

| Approvals / Certificates                                |          |                                                            |
|---------------------------------------------------------|----------|------------------------------------------------------------|
| General approvals                                       |          | Declarations of conformity and manufacturer's declarations |
| <div><div>CCA</div><div>KEMA<br/>KEUR</div></div>       |          |                                                            |
| Approval                                                | Standard | Certificate Name                                           |
| CCA<br>DEKRA Certification B.V.                         | EN 61535 | NTR NL-7971                                                |
| KEMA/KEUR<br>DEKRA Certification B.V.                   | EN 61535 | 71-123232                                                  |
| Approval                                                | Standard | Certificate Name                                           |
| EU-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                                                          |
| UK-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                                                          |



Downloads

Environmental Product Compliance

|                                  |  |  |   |
|----------------------------------|--|--|---|
| Compliance Search                |  |  |   |
| Environmental Product Compliance |  |  | ↓ |
| 891-8995/206-502                 |  |  |   |

Documentation

|                  |            |                 |   |
|------------------|------------|-----------------|---|
| Bid Text         |            |                 |   |
| 891-8995/206-502 | 19.02.2019 | xml<br>2.98 KB  | ↓ |
| 891-8995/206-502 | 01.12.2014 | doc<br>25.00 KB | ↓ |

CAD/CAE-Data

|                                       |   |
|---------------------------------------|---|
| CAE data                              |   |
| EPLAN Data Portal<br>891-8995/206-502 | ↓ |
| WSCAD Universe<br>891-8995/206-502    | ↓ |

1 Compatible Products

1.1 Required Accessories

1.1.1 Locking system

1.1.1.1 Locking system



[Item No.: 890-111](#)  
Locking lever; for flying leads; for tool operation; black



[Item No.: 890-131](#)  
Locking lever; for flying leads; for tool operation; white



[Item No.: 890-101](#)  
Locking lever; for manual operation; black



[Item No.: 890-121](#)  
Locking lever; for manual operation; white

1.2 Optional Accessories

1.2.1 Cover

1.2.1.1 Cover



[Item No.: 897-2003](#)  
Protective cap; Type2; for sockets and plugs; PVC; red



1.2.2 Installation

1.2.2.1 Mounting accessories



**Item No.: 890-310**  
Mounting carrier; 2- to 5-pole; for flying leads; black

**Item No.: 890-311**  
Mounting carrier; 2- to 5-pole; for flying leads; white