



Color: ☐ transparent

WAGO's 750-106 and 750-107 Marker Carriers allow I/O functions to be identified throughout the node via continuous marking strips. Both carrier models permit continuous marking regardless of the I/O module housing used.

- 750-106, for I/O module housing with up to 4 LEDs, as well as for 48 mm I/O module housing
- 750-107, for I/O module housing with 8 or 16 LEDs

The marker carrier can be accommodated in the upper Mini-WSB marker slot. It is not necessary to use a carrier on each I/O module to mount the marking strip.

Technical data		
Suitable		for I/O module housing with up to 4 LEDs and for the 48 mm I/O module housing
Insulation material (main housing)		Polycarbonate (PC)
Flammability class per UL94		V2

Material data		
Color		transparent
Weight		0.4 g
Fire load		0.016 MJ

Commercial data		
Product Group		15 (I/O System)
eCl@ss 10.0		27-14-40-75
eCl@ss 9.0		27-37-12-29
ETIM 9.0		EC002248
ETIM 8.0		EC002248
PU (SPU)		50 (10) pcs
Packaging type		Box
Country of origin		DE
GTIN		4050821608684
Customs tariff number		39269097900



Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 750-106	↓

Documentation

Bid Text			
750-106	19.02.2019	xml 3.39 KB	↓
750-106	09.01.2019	docx 14.82 KB	↓

CAD/CAE-Data

CAD data		CAE data	
2D/3D Models 750-106	↓	EPLAN Data Portal 750-106	↓
		WSCAD Universe 750-106	↓
		ZUKEN Portal 750-106	↓

1 Compatible Products

1.1 Required Accessories

1.1.1 Marking

1.1.1.1 Marker



Item No.: 2009-115
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

1.1.1.2 Marking strip



Item No.: 2009-110
Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white



Installation Notes

Application

