





Color:   white



Dimensions in mm

Cable assembly *WINSTA*® MINI with strain relief

Use effective pluggable connections instead of laborious screw connections: With the *WINSTA*® MINI cable assembly A coding. On PCBs, in control cabinets or for connecting lights – pluggable installation connectors from WAGO allow you to establish connections according to a huge variety of requirements in seconds. For greater protection in electrical installations, the pluggable installation connector is equipped with mechanical protection against mismatching. The pluggable installation connector is protected in accordance with protection type IP40. Users' hands and tools will never come into contact with live elements. Thanks to the color coding and mechanical A coding of *WINSTA*® MINI pluggable installation connectors, you can clearly distinguish different circuits. *WINSTA*® MINI is our response to the trend toward miniaturisation. Our smallest pluggable connection system is especially suitable for lights, for instance, since as a result of LED technology; due to complex systems, these offer less and less space for the connection technology. This product meets all the relevant safety requirements of fire class E; thus it can be used in areas where fire safety is relevant. Not using halogen additives in the manufacture of this cable assembly significantly increases fire safety and minimises environmental pollution.

Pluggable connections instead of screw connections – cable assemblies from WAGO

The cable assembly is equipped with a socket and a free end. The *WINSTA*® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and thus more efficient, more reliable, and error-free. Use of this pre-assembled system decreases assembly times and installation errors at the construction site. Choose durability and quality – with marking from WAGO makes the electrical installation of electrical components significantly easier.

- protection against mismatching eliminates errors
- consistent IP40 protection
- for any mains application
- ready for immediate use
- fast, secure installation

| Notes |                                                               |
|-------|---------------------------------------------------------------|
| Note  | Cables with a different fire class can be found in the eShop. |

| Electrical data      |       |                |    |  | General information                             |  |
|----------------------|-------|----------------|----|--|-------------------------------------------------|--|
| Ratings per          |       | IEC/EN 60664-1 |    |  | Note on contact resistance                      |  |
| Overvoltage category | III   | III            | II |  | approx. 1 mΩ of contact resistance              |  |
| Pollution degree     | 3     | 2              | 2  |  | approx. 0.25 mΩ contact transition plug/ socket |  |
| Nominal voltage      | 400 V | -              | -  |  |                                                 |  |
| Rated surge voltage  | 6 kV  | -              | -  |  |                                                 |  |
| Rated current        | 13 A  | -              | -  |  |                                                 |  |



| Connection data            |                           |                                 |                    |
|----------------------------|---------------------------|---------------------------------|--------------------|
| Total number of potentials | 5                         | Connection 1                    |                    |
| Conductor preparation      | ultrasonically tip-bonded | Strip length                    | 9 mm / 0.35 inches |
|                            |                           | Pole number                     | 5                  |
|                            |                           | Wire cross-section              | 1.5 mm²            |
|                            |                           | Strip length (outer insulation) | 45 mm              |
|                            |                           | Connection type                 | Socket - free end  |

| Physical data |  |                        |
|---------------|--|------------------------|
| Pin spacing   |  | 4.4 mm / 0.173 inches  |
| Width         |  | 26.7 mm / 1.051 inches |
| Height        |  | 15.8 mm / 0.622 inches |
| Total length  |  | 4 m                    |

| Mechanical data                         |  |                                                               |
|-----------------------------------------|--|---------------------------------------------------------------|
| Use                                     |  | General mains applications                                    |
| Coding                                  |  | A                                                             |
| Variable coding                         |  | No                                                            |
| Marking                                 |  | N ⊕ 1 2 3                                                     |
| Potential marking                       |  | N ⊕ 1 2 3                                                     |
| Mating force of a plug-in connection    |  | approx. 20 ... 70 N (depending on pole number)                |
| Retention force of a plug-in connection |  | when locked: > 80N                                            |
| Unmating force of a plug-in connection  |  | when unlocked: approx. 20 ... 70 N (depending on pole number) |
| Number of mating cycles                 |  | 200, without resistive load                                   |
| Connection type                         |  | Socket - free end                                             |
| Type of pre-assembled cable             |  | Connecting cable                                              |
| Cable type                              |  | H05Z1Z1-F 5G1.5                                               |
| Protection type                         |  | IP40                                                          |

| Plug-in connection            |  |                                                                                                                                                                                                                                                                                                                  |
|-------------------------------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mismating protection          |  | Yes                                                                                                                                                                                                                                                                                                              |
| Note on mismating protection  |  | All <i>WINSTA</i> ® components are 100% protected against mismating when:<br>a.) plugging different numbers of poles<br>b.) plugging while rotated 180<br>c.) plugging while laterally staggered<br>d.) plugging one pole                                                                                        |
| Locking lever                 |  | Can be retrofitted                                                                                                                                                                                                                                                                                               |
| Locking of plug-in connection |  | Locking lever                                                                                                                                                                                                                                                                                                    |
| Note on locking system        |  | All connectors for mounted installations (snap-in versions for lighting fixtures or devices, all types of PCB and distribution connectors) are factory-equipped with locking levers to ensure plugs and sockets are securely locked. Additional locking levers are only required for flying leads (plug/socket). |

| Material data                      |  |                                                                          |
|------------------------------------|--|--------------------------------------------------------------------------|
| Note (material data)               |  | <a href="#">Information on material specifications can be found here</a> |
| Color                              |  | white                                                                    |
| Insulation material (main housing) |  | Polyamide (PA66)                                                         |
| Fire class per EN 50575            |  | E <sub>ca</sub>                                                          |
| Contact material                   |  | Copper or copper alloy; surface-treated                                  |
| Contact Plating                    |  | Tin                                                                      |
| Fire load                          |  | 119.984 MJ                                                               |
| Connector color                    |  | white                                                                    |
| Strain relief color                |  | white                                                                    |



| Material data                    |              |
|----------------------------------|--------------|
| Sheathed cable color             | white        |
| Printing color of sheathed cable | black        |
| Halogen-free                     | Yes          |
| Silicon-free                     | Yes          |
| Sheath material                  | Halogen-free |
| Rubber cable                     | No           |
| Weight                           | 626.9 g      |
| Copper weight of the pipe        | 0.072 kg/m   |

| Environmental requirements               |                                                                                                       |
|------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Processing temperature                   | -5 ... +40 °C                                                                                         |
| Continuous operating temperature         | -35 ... +85 °C                                                                                        |
| Note on continuous operating temperature | Cable for temperatures ≤ 70 °C (including halogen-free)<br>Insulating parts for temperatures ≤ 105 °C |

| Commercial data       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-44-06-04   |
| eCl@ss 9.0            | 27-44-06-04   |
| ETIM 9.0              | EC002587      |
| ETIM 8.0              | EC002587      |
| PU (SPU)              | 1 pcs         |
| Packaging type        | unpacked      |
| Country of origin     | PL            |
| GTIN                  | 4055143400169 |
| Customs tariff number | 85444290900   |

| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

| Approvals / Certificates |                                                            |
|--------------------------|------------------------------------------------------------|
| General approvals        | Declarations of conformity and manufacturer's declarations |



| Approval                              | Standard | Certificate Name |
|---------------------------------------|----------|------------------|
| CCA<br>DEKRA Certification B.V.       | EN 61535 | NTR NL-7971      |
| KEMA/KEUR<br>DEKRA Certification B.V. | EN 61535 | 71-123232        |

| Approval                                                | Standard | Certificate Name |
|---------------------------------------------------------|----------|------------------|
| EU-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                |
| UK-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                |



Downloads

Environmental Product Compliance

|                                  |  |  |   |
|----------------------------------|--|--|---|
| Compliance Search                |  |  |   |
| Environmental Product Compliance |  |  | ↓ |
| 891-8995/116-402                 |  |  |   |

Documentation

|                  |            |                 |   |
|------------------|------------|-----------------|---|
| Bid Text         |            |                 |   |
| 891-8995/116-402 | 19.02.2019 | xml<br>3.01 KB  | ↓ |
| 891-8995/116-402 | 01.12.2014 | doc<br>25.00 KB | ↓ |

CAD/CAE-Data

|                                       |   |
|---------------------------------------|---|
| CAE data                              |   |
| EPLAN Data Portal<br>891-8995/116-402 | ↓ |
| WSCAD Universe<br>891-8995/116-402    | ↓ |

1 Compatible Products

1.1 Required Accessories

1.1.1 Locking system

1.1.1.1 Locking system



[Item No.: 890-111](#)  
Locking lever; for flying leads; for tool operation; black



[Item No.: 890-131](#)  
Locking lever; for flying leads; for tool operation; white



[Item No.: 890-101](#)  
Locking lever; for manual operation; black



[Item No.: 890-121](#)  
Locking lever; for manual operation; white

1.2 Optional Accessories

1.2.1 Cover

1.2.1.1 Cover



[Item No.: 897-2003](#)  
Protective cap; Type2; for sockets and plugs; PVC; red



1.2.2 Installation

1.2.2.1 Mounting accessories



**Item No.: 890-310**  
Mounting carrier; 2- to 5-pole; for flying leads; black

**Item No.: 890-311**  
Mounting carrier; 2- to 5-pole; for flying leads; white