



Color: ■ white

Technical data	
Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	800 pcs/reel; 2 lines
Properties	Inner wrap (inside marking area)
Printing device	Smart Printer (thermal transfer printer)
Physical data	
Height	15 mm
Width	117.5 mm
Depth	0.17 mm
Marking surface	100 x 15 mm
Mechanical data	
Mounting type	Mounting with cable ties
Smear resistance	in conjunction with 258-5005 Ink Ribbon
Material data	
Color	white
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	600 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (storage)	+10 ... +21 °C
Ambient temperature (operation)	-30 ... +120 °C
Relative humidity	40 ... 50 %

Commercial data	
eCl@ss 10.0	27-40-04-01
eCl@ss 9.0	27-40-04-01
ETIM 9.0	EC001530
ETIM 8.0	EC001530
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143040891
Customs tariff number	39269097900

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 211-836

↓

Documentation

Operating Instructions

211-836 Information on printing material128.08.2020pdf1467.39 KB

↓

1 Compatible Products
1.2 Optional Accessories
1.2.1 Marking
1.2.1.1 Marking device



Item No.: 258-5000
Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material