





Similar to illustration



Notes	
Safety Information	Notice! Live parts can be easily touched! Protection against direct contact must be provided by the equipment manufacturer, e.g., using a WAGO 709 Series Cover (see "Accessories") or a similar cover. The installation guidelines must be observed for each individual application.

Electrical data	
Operating voltage	≤ 30 VAC; ≤ 50 VDC
Nominal current	1 A

Safety and protection	
Rated Voltage	50 V
Rated impulse withstand voltage	0.8 kV
Pollution degree	2
Protection type	IP00
Insulation type	Basic insulation

Connection data	
Performance level	3 / 50 mating cycles
Connection 1	
Pluggable connector	DIN 41651 connector; male connector
Pole number 1	16
Connection type 1	System
Note (conductor cross-section)	12 AWG: THHN, THWN
Mating direction	vertical

Connection 2	
Design 2	PCB terminal blocks (double-row)
Pole number 2	16
Connection type	Field
Connection technology	CAGE CLAMP®
WAGO connector 2	WAGO 236 Series
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG

Connection 2	
Strip length	5 ... 6 mm / 0.2 ... 0.24 inches



Physical data		
Width		56.5 mm / 2.224 inches
Height		63.5 mm / 2.5 inches
Depth from upper-edge of DIN-rail		28 mm / 1.102 inches

Mechanical data		
Mounting type		DIN-35 rail
Housing design		PCB with mounting feet

Material data		
Contact material (connector)		Au over Ni
Fire load		0.056 MJ
Weight		33 g

Environmental requirements		
Ambient temperature (operation)		-20 ... +55 °C
Ambient temperature (storage)		-40 ... +70 °C
Relative humidity		≤ 85 % (non-condensing)

Standards and specifications		
Standards/specifications		EN 61010-2-201

Commercial data		
Product Group		6 (INTERFACE ELECTRONIC)
eCl@ss 10.0		27-14-11-52
eCl@ss 9.0		27-14-11-52
ETIM 9.0		EC002780
ETIM 8.0		EC002780
PU (SPU)		10 (1) pcs
Packaging type		Box
Country of origin		DE
GTIN		4045454759209
Customs tariff number		85366990990

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 289-403

↓

Documentation

Bid Text

289-403

19.02.2019

xml

3.26 KB

↓

289-403

09.02.2015

doc

25.00 KB

↓

Instruction Leaflet

pdf

1246.19 KB

↓

CAD/CAE-Data

CAD data

2D/3D Models 289-403

↓

CAE data

EPLAN Data Portal 289-403

↓

WSCAD Universe 289-403

↓

ZUKEN Portal 289-403

↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Installation

1.1.1.1 Cover



Item No.: 709-153
Cover; Type 1; suitable for cover carrier, type 1; 1 m long; transparent

1.1.1.2 Cover carrier

Item No.: 709-167
Cover carrier; Type 1; incl. fixing/retaining screws and knurled nut; suitable for 279 to 282 and 880 Series rail-mounted terminal blocks; suitable for 264 Series miniature rail-mounted terminal blocks; suitable for 270 Series sensor and actuator terminal blocks; gray

1.1.2 Tool

1.1.2.1 Operating tool




Item No.: 210-720


Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

Installation Notes

Conductor termination



Conductor termination – screwdriver actuation parallel to conductor entry



Conductor termination – screwdriver actuation perpendicular to conductor entry