

# PRODUCT DATASHEET Decor Plaster Nest Pendant 3XG9 White

Decor Plaster | Decorative luminaires made of plaster with exchangeable light source



### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

### **Product benefits**

- High-quality look and feel
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Easy mounting
- Real wood used by some types

### **Product features**

- Housing material: metal and plaster
- Textile cable




## **TECHNICAL DATA**

## Electrical data

| Nominal voltage  | 220240 V                                  |
|------------------|---|
| Mains frequency  | 5060 Hz                                   |
| Protection class | T. C. |
| Operating mode   | Mains voltage                             |

# Dimensions & Weight

| Length         | 500.00 mm  |
|----------------|------------|
| Width          | 385.00 mm  |
| Height         | 1500.00 mm |
| Product weight | 3700.00 g  |



# DECOR PLASTER NEST PEND 3XG9 WT

# Materials & Colors

| Product color  | White   |
|----------------|---------|
| Housing color  | White   |
| Body material  | Plaster |
| Cover material | Glass   |

# **Application & Mounting**

| Ambient temperature range              | -20+40 °C                   |  |
|--|-----------------------------|--|
| Temperature range at storage           | -20+80 °C                   |  |
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |  |
| Type of protection                     | IP20                        |  |
| Protection class IK (shock resistance) | IK03                        |  |
| Dimmable                               | No                          |  |

| Mounting type           | Suspended |
|-------------------------|-----------|
| Application environment | Indoor    |
| With light source       | No        |
| Holder designation      | G9        |

### Certificates & Standards

| Standards  | CE / UKCA |
|--|-----------|
| Luminaire with limited surface temperature, "D sign" | No        |

## Additional product data

| Product remark        | Maximum bulb wattage: 5 W LED |  |
|-----------------------|-------------------------------|--|
| Number of illuminants | 3                             |  |

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

## DOWNLOAD DATA

|     | Documents and certificates             | Document name                               |
|-----|--|---|
| PDF | User instruction / safety instructions | DECOR CLAY/CONCRETE/PLASTER NEST PENDANT G9 |
| PDF | Declarations of conformity             | DECOR LUM                                   |
| PDF | Declarations of conformity UKCA        | DECOR LUM                                   |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075841420 | Folding box                  | 144 mm x 452 mm x 693 mm             | 4315.00 g    | 45.11 dm <sup>3</sup> |
| 4058075841437 | Shipping box 2               | 470 mm x 302 mm x 718 mm             | 9874.00 g    | 101.91 dm³            |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.