

PRODUCT DATASHEET

DL SLIM ALU D150 V 13W MS 840 WT

DOWNLIGHT SLIM ALU | Very slim downlights with aluminum housing and luminous efficacy up to 100 lm/W



Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

Product benefits

- Low installation depth
- Highly versatile due to selectable CCT and power steps (Multi Color / Multi Lumen)
- Very homogenous light distribution
- External driver with 3-pole through-wiring feature for flexibility and easy installation
- Emergency lighting possible with LEDVANCE Emergency Conversion Box
- Energy savings up to 60 % (compared to luminaires that use CFL lamps)

Product features

- Very slim aluminum housing with only 23 mm height
- High luminous efficacy: up to 100 lm/W
- Multi Lumen function: power steps selectable
- Multi Color function: 4000K and 3000K
- Type of protection: IP44
- Luminaire available in 5 sizes for different cut-outs
- Lifetime (L70/B50): 50,000 h (temperature at $T_a = 40\text{ °C}$)




TECHNICAL DATA**Electrical data**


Nominal wattage	13 W / 9.8 W / 6.5 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	58/45/33 mA
Inrush current	6 A
Inrush current time T_{h50}	30 μ s
Max. number of luminaires per miniature circuit breaker B16	70
Max. number of luminaires per miniature circuit breaker C10	45
Max. number of luminaires per miniature circuit breaker C16	80
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	External LED driver

Photometrical data


Luminous flux	1300 lm / 980 lm / 650 lm
Luminous efficacy	100 lm/W
Color temperature	3000 K / 4000 K
Reference control setting of contained light source (Kelvin)	4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Luminous intensity	-
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG1
Beam angle	90 °




DL SLIM ALU D150 V 13W MS 830
WT



DL SLIM ALU D150 V 13W MS 840
WT



DL SLIM ALU D150 V 13W MS 830
WT




DL SLIM ALU D150 V 13W MS 840
WT

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
13 W	3000 K	1300 lm	100 lm/W
13 W	4000 K	1300 lm	100 lm/W
9.8 W	3000 K	980 lm	100 lm/W
9.8 W	4000 K	980 lm	100 lm/W
6.5 W	3000 K	650 lm	100 lm/W
6.5 W	4000 K	650 lm	100 lm/W

Dimensions & Weight

Diameter	162.00 mm
Height	23.00 mm
Product weight	280.00 g



DL SLIM ALU D150 V

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+85 °C
Type of connection	Screwless terminal, 3-Pole (N, E, L)
Type of protection	IP44/IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling / Wall
Application environment	Indoor
Mounting diameter	150 mm
Mounting depth	23 mm
Adjustable	No

With light source	Yes
-------------------	-----

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Lifespan L80/B10 at 25 °C	35000 h ¹⁾
Lifespan L80/B50 at 25 °C	35000 h
Lifespan L90/B10 at 25 °C	15000 h
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	240 mA
ECG - Output ripple current	< 10 %
ECG - Length	100 mm
ECG - Width	49 mm
ECG - Height	26 mm

Certificates & Standards

Standards	CE / UKCA / EAC / ENEC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from March 2025
Added function	MULTI SELECT

Accessories Optional

Product image	Product name	EAN
---------------	--------------	-----



DL SLIM ALU FRAME D150 WT

4099854475986

EQUIPMENT / ACCESSORIES


– Accessories for surface mounting available

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DOWNLIGHT SLIM ALU
	Legal information	LSI DL SLIM ALU ON\OFF
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety Insert G11207793
	Legal information	SP VARIO DN170
	Legal information	DL SLIM ALU
	Declarations of conformity	DL SLIM ALU
	Declarations of conformity UKCA	DL SLIM ALU
Photometric and lighting design files		Document name
	IES file (IES)	DL SLIM ALU D150 V 13W MS 830 WT
	IES file (IES)	DL SLIM ALU D150 V 13W MS 840 WT
	LDT file (Eulumdat)	DL SLIM ALU D150 V 13W MS 830 WT
	LDT file (Eulumdat)	DL SLIM ALU D150 V 13W MS 840 WT
	UGR file (UGR table)	DL SLIM ALU D150 V 13W MS 830 WT
	UGR file (UGR table)	DL SLIM ALU D150 V 13W MS 840 WT
	Light distribution curve type cone	DL SLIM ALU D150 V 13W MS 830 WT
	Light distribution curve type cone	DL SLIM ALU D150 V 13W MS 840 WT
	Light distribution curve type polar	DL SLIM ALU D150 V 13W MS 830 WT
	Light distribution curve type polar	DL SLIM ALU D150 V 13W MS 840 WT

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854441790	Folding box 1	57 mm x 118 mm x 118 mm	336.00 g	0.79 dm³
4099854441806	Shipping box 12	358 mm x 349 mm x 192 mm	4450.00 g	23.99 dm³

ADDITIONAL CATALOG INFORMATION



– For Guarantee see www.ledvance.com/guarantee

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.