

PRODUCT DATASHEET

FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW

FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW | Interface for standard lighting switches, control of up-to 32 lights and up-to 4 sensors/pushbutton couplers, installation in standard flush mounted boxes, enables Tunable White lighting



Areas of application

- Single room lighting up to 300 sqm with one control unit
- Up to 4 entrance and exit areas can be manually controlled in a synchronized manner
- Connection of light and presence sensors for automated light control
- RGB and Tunable white applications

Product benefits

- Compatible with standard light switches
- Easy Scene creation via App
- Simplified startup thanks to predefined operation modes
- Integrated DALI supply
- Adjustment of all settings via smartphone
- Up to 4 groups separately controllable
- Support of swarm function

Product features

- DALI-2 certified compact control unit for up-to 32 lights and up-to 4 sensors/pushbutton couplers
- Installation in standard flush-mounted boxes
- Pushbutton interface to separately control brightness and color temperature
- One DALI output channel (Broadcast or Groupcast)
- Supports DALI DT8 Tunable White driver
- Smart phone connection via Bluetooth to control and configure

- Cable length of the DALI control cable: up to 300 m
- Length of the pushbutton cable: up to 50 m

TECHNICAL DATA

Electrical data

Nominal wattage	3.00 W
Nominal voltage	220...240 V
Type of current	DC
Input current	22 mA
Mains frequency	50...60 Hz
Operating frequency	50/60 Hz

Dimensions & Weight



Length	49.00 mm
Width	48.00 mm
Height	22.00 mm
Wire preparation length, input side	5...6 mm
Product weight	40.00 g

Colors & materials

Product color	Light grey
---------------	------------

Temperatures & operating conditions

Ambient temperature range	-20...+60 °C
Maximum temperature at tc test point	70 °C
Temperature range in operation	-20...+60 °C

Lifespan

Number of switching cycles	30000
----------------------------	-------

Additional product data

Number of control outputs	1
Max. connectable push button couplers / sensors	4
Max. number of connected drivers	32
Commissioning App	App (Android/ iOS)
Light control tool App	App (Android/ iOS)
Groups	4

Capabilities

Dimmable	No
Dimming interface	DALI-2
Number of control outputs	1
Type of installation	Integrated in flush device box

Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

– App for iOS and Android available for free in the app store

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	FLEX CU FLUSH MOUNT DALI 2 TW
 User instruction / safety instructions	FLEX CU FLUSH MOUNT DALI-2 TW
 Extended installation guide	Application Guide FLEX Control Units DALI2
 On-Pack-Info	Privacy Information LEDVANCE DALI CONFIG APP EN
 On-Pack-Info	Privacy Information LEDVANCE DALI CONTROL APP EN
 Legal information	Informationstext 18 Abs 4 ElektroG
 Declarations of conformity	FLEX CU FLUSH MOUNT DALI-2 TW

Tender texts	Document name
 Tender documents	DALI-2 CONTROL UNITS FLUSH MOUNT DALI-2 TW-EN


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075841901	Folding box 1	81 mm x 81 mm x 46 mm	57.00 g	0.30 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075841918	Shipping box 60	344 mm x 254 mm x 278 mm	3847.00 g	24.29 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For current information see www.ledvance.com/light-management-systems

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.