

PRODUCT DATASHEET

BLKH RD EL 250 P 12W MS 840 BK

BULKHEAD ROUND EMERGENCY | Robust wall and ceiling luminaire with IP65 and IK10 protection and emergency lighting function



Areas of application

- Emergency illumination of escape routes
- Antipanic lighting
- Buildings requiring up to 3 h emergency light operation
- Direct replacement for luminaires with fluorescent lamps
- Corridors, stairways, entrance areas
- Passages, underpasses
- Public areas

Product benefits

- Seamless integration of luminaires with emergency lighting function into general lighting
- Easy wiring thanks to included prewired driver and battery for Emergency lighting function
- Simple testing of luminaires with emergency lighting function thanks to integrated automatic test function
- Operation of integrated emergency lighting function with long life LiFePO4 battery with 3h battery discharge time
- Convenient visualization of results of automatic test with an included control LED
- Highly versatile due to selectable CCT and power steps (Multi Color / Multi Lumen) on the driver
- Flexible mounting patterns for convenient installation
- Suitable for use in dusty and damp locations thanks to high IP rating
- Suitable for use in public areas thanks to high IK rating
- Separate decor element available for an aesthetic and functional product design

Product features

- Certified according to European norms (EN 60598-2-22)
- Luminaire suited for normal lighting and emergency lighting



- Self-contained luminaires
- Emergency lighting function: battery discharge time of 3 h
- Function test of emergency lighting: automatic (AT)
- Battery technology: LiFePO₄
- Ambient temperature in operation: 0...+35 °C
- UV-stabilized polycarbonate (PC) housing, PC-diffuser
- Impact resistance: IK10
- Type of protection: IP65

TECHNICAL DATA

Electrical data


Nominal wattage	12 W / 11 W / 9.5 W / 8.5 W ¹⁾
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	59mA / 54mA / 49mA / 45 mA
Inrush current	3.38 A
Inrush current time T _{h50}	21.2 µs
Max. number of luminaires per miniature circuit breaker B16	213
Max. number of luminaires per miniature circuit breaker C10	133
Max. number of luminaires per miniature circuit breaker C16	213
Power factor λ	> 0.80
Total harmonic distortion	< 15 %
Protection class	II
Surge capability (L-N)	1000 V
Operating mode	Integrated LED driver

¹⁾ For possible options refer to lumen/power table image


Photometrical data

Luminous flux	1230 lm / 1080 lm / 860 lm / 710 lm ¹⁾
Luminous efficacy	102 lm/W / 98 lm/W / 90 lm/W / 84 lm/W ¹⁾
Color temperature	3000 K / 4000 K
Reference control setting of contained light source (Kelvin)	4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	5 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °


¹⁾ For possible options refer to lumen/power table image




BLKH 250 P 10W 830 1200lm



BLKH 250 P 10W 840 1200lm



BLKH 250 P 10W 840 1200lm




BLKH 250 P 10W 830 1200lm

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
12 W	3000 K	1160 lm	96 lm/W
12 W	4000 K	1230 lm	102 lm/W
11 W	3000 K	1030 lm	94 lm/W
11 W	4000 K	1080 lm	98 lm/W
9.5 W	3000 K	830 lm	88 lm/W
9.5 W	4000 K	860 lm	90 lm/W
8.5 W	3000 K	680 lm	81 lm/W
8.5 W	4000 K	710 lm	84 lm/W

Dimensions & Weight

Diameter	262.00 mm
Height	73.00 mm
Product weight	930.00 g



BLKH RD/SEN/EM 250 P 10W CPS

Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0...+35 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Outdoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	97000 h ¹⁾
Lifespan L80/B10 at 25 °C	72000 h ¹⁾
Lifespan L80/B50 at 25 °C	65000 h

Lifespan L90/B10 at 25 °C	46000 h
Number of switching cycles	100000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	350...300...250...200 mA
ECG - Output ripple current	< 5 %

BATTERY

Type of Battery	LiFePO4
Battery size [GMS]	Others
Nominal voltage of battery	3.2 V
Nominal capacity of battery	4500 mAh
Battery charging time	24 h

Emergency lighting

Type of Emergency Lighting (EL)	EL unit (battery and controller) for decentral operation included
Area of emergency application	Anti-panic lighting / Escape route lighting
Type of emergency light operation	Non-maintained / Maintained
Type of emergency operation test	Automatic
Wattage in maintained operation mode	12 W
Wattage in emergency operation mode	2.3 W
Luminous flux in maintained operation mode	1230 lm
Luminous flux in emergency operation mode	380 lm
Battery life in emergency operation mode	3 h
Integrated test switch	No

Certificates & Standards

Standards	CE / CB / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Only by an expert

Additional product data

Product remark	Available from June 2025
Added function	EVERLOOP / MULTI SELECT

Accessories Optional

Product image	Product name	EAN
	BLKH RD Eyelid 250 WT	4099854286773
	BLKH RD Eyelid 250 BK	4099854286759
	LISOEV 250R 8W 830 840 BLKH	4099854311918
	DR DS-P- 10/220-240/350 BLKH	4099854286834

EQUIPMENT / ACCESSORIES

- Additional cover rings in different designs available
- Mounting screws and dowels included
- Anti-theft screw included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	BULKHEAD RD EMERGENCY AND SENSOR
 Legal information	Informationstext 18 Abs 4 ElektroG
 Legal information	Safety Insert G11234787
 Legal information	Legal Insert G11234785

Documents and certificates		Document name
	Legal information	Light Source Insert G11232870
	Declarations of conformity	BLKH RD
	Declarations of conformity UKCA	BLKH RD

Photometric and lighting design files		Document name
	IES file (IES)	BLKH 250 P 10W 830 1200lm
	IES file (IES)	BLKH 250 P 10W 840 1200lm
	LDT file (Eulumdat)	BLKH 250 P 10W 830 1200lm
	LDT file (Eulumdat)	BLKH 250 P 10W 840 1200lm
	UGR file (UGR table)	BLKH 250 P 10W 830 1200lm
	UGR file (UGR table)	BLKH 250 P 10W 840 1200lm
	Light distribution curve type cone	BLKH 250 P 10W 830 1200lm
	Light distribution curve type cone	BLKH 250 P 10W 840 1200lm
	Light distribution curve type polar	BLKH 250 P 10W 830 1200lm
	Light distribution curve type polar	BLKH 250 P 10W 840 1200lm



CAD/BIM files		Document name
	BIM Revit 3D	Bulkhead Round
	CAD STEP 3D	BLKH G2 250

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854286285	Folding box 1	77 mm x 266 mm x 266 mm	1136.00 g	5.45 dm³
4099854286292	Shipping box 8	545 mm x 280 mm x 335 mm	9638.00 g	51.12 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.