



PRODUCT DATASHEET

FLASHLIGHT TACTICAL IP65

FLASHLIGHT TACTICAL IP65 | Outdoor mobiles

Areas of application

- Multifunctional

Product benefits

- 4 operating modes: 1 press: bright light 1400 lm, 2nd press: soft light 450 lm, 3rd press: SOS mode, 4th press: flashing mode
- The angle of the light beam is adjusted by turning the lens
- 4 hours of running at full brightness
- Powered by 6 AAA batteries (not included)
- Type of protection: IP65 (with closed rotary lens adjustment mechanism)

Product features

- Sturdy aluminum housing
- Convenient button for switching modes

TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
Inrush current	1.8 A
Inrush current time T _{h50}	0.5 s
Operating mode	Battery

Photometrical data

Luminous flux	1400 lm
Luminous efficacy	93 lm/W
Color temperature	6500 K
Light color (designation)	Cool White
Color rendering index Ra	70

Dimensions & Weight

Diameter	50.00 mm
Height	197.00 mm
Product weight	510.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP65/IP20
Dimmable	No
Adjustable	No
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

Documents and certificates		Document name
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	FLASHL

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854175848	Folding box 1	59 mm x 59 mm x 206 mm	536.00 g	0.72 dm ³
4099854175855	Shipping box 24	367 mm x 253 mm x 235 mm	13513.00 g	21.82 dm ³
4099854584008	Shipping box 6	290 mm x 190 mm x 175 mm	3528.00 g	9.64 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.