

PRODUCT DATASHEET LS AY AC-CD P2 200 P

CONNECTOR FOR LED DRIVER | LED strip connector for LED driver connection



Areas of application

- General indoor illumination
- General outdoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Simple and quick installation thanks to twist lock functionality

Product features

- Safe and professional connector of LED strips via integrated over-current protection (3.15A)
- Suitable for connection with LED driver DR P 500W 220-240V 215V P
- Type of protection: IP66

TECHNICAL DATA

Electrical data

Туре о	fcurrent	DC

Dimensions & Weight



Length	300.0 mm
Width	22.0 mm
Height	20.0 mm
Product weight	56.00 g

Colors & materials

Product color	White
Body material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20+45 °C
Temperature range in operation	-20+45 °C
Permitted rel. humidity during operation	093 %

Additional product data

Product remark	Available from September 2024
----------------	-------------------------------

LOGISTICAL DATA

	Temperature range at storage	-20+80 °C
--	------------------------------	-----------

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	UI_LED STRIP_HV
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert G11201420

	Documents and certificates		Document name
PDF	Declarations of conformity		LS LUM
PDF	Declarations of conformity UKCA		LS LUM
	Tender texts	Document name	

Tender documents CONNECTOR FOR LED DRIVER P2 200 P-en


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075844742	BAG 1	200 mm x 250 mm x 20 mm	72.00 g	1.00 dm ³
4058075844759	Shipping box 50	347 mm x 347 mm x 174 mm	4093.00 g	20.95 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION





DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.