

Features

- Simple and slick integral design with no driver box and without any visible screws

New technology utilization for improved performance
Extremely precise light beams due to the high-quality lenses #80mm die-cast aluminium body, Fix beam angle: 55° , Textured black finishing colour Light color temperature: 4000K, natural light System power: 18W, Fixture lumen output: 1600lm, efficacy: 89lm/W, Ra97 typical, LED chromacity: 2 step MacAdam ellipse LED source (SDCM2), IR/UV free light source without heat radiation Operating voltage 220-240V / 50-60Hz, electronic driver, DALI dimmable Surface mounting with surface mounting base. Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only Horizontal rotation: 355°, vertical tilt: 90° Nominal product dimensions: D.80mmx200mm 5 years warranty. Suitable for ceiling surface mounting, and wall surface mounting


Product Overview

Product name	CONCORD BEACON 4000K SM WIDE DALI BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Wall surface mounted
Fixture rating	Enclosed
General application	Museums & Galleries, Retail, Hospitality
ETIM Class	EC001744
Fixture luminous flux (lm)	1600
Luminaire efficacy (lm/W)	89
LOR (%)	100
Correlated colour temperature (k)	4000

CONCORD BEACON 4000K SM WIDE DALI BLACK 2062558

Light colour	Neutral White
CRI (Ra)	97
Colour Variation Initial (SDCM)	2
Beam Angle (°)	55
Photobiological Risk Group	RG1
Total power consumption (W)	18
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	RAL9005
IP rating	IP20
IK rating	IK02
Product EAN number	5025768625581
Warranty	5 years
Dimming method	DALI
Useful luminous flux (#use)	1550

Photometry



Technical drawings

