

START Downlight Flat 108 IP44 550LM 830 DIM
0054118



Features

- START Downlight Flat IP44 DIM is an integrated LED recessed downlight with a separate phase dimmable driver and Loop in out box; 7W; 550Lm; 79Lm/W; 3000K; IP44 rated from the front


Product Overview

Product name	START Downlight Flat 108 IP44 550LM 830 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278490
Fixture luminous flux (lm)	550
Luminaire efficacy (lm/W)	78
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	7
Electrical protection	Class II
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9003

START Downlight Flat 108 IP44 550LM 830 DIM 0054118

IP rating	IP44/20
IK rating	IK06
Product EAN number	5410288541181
Warranty	5 years
Dimming method	Mains: leading / trailing edge
Useful luminous flux (#use)	550

Photometry



Technical drawings

