



Features

- Ceiling / wall luminaire with integrated LED. Perfect solution for hallways, circulation spaces or foyer. Even and uniform light distribution with a halo lighting effect on the wall surface. Body Size diameter 250mm. Besa mounting box compatible, hole distance 51mm. DualTone functionality enables switch between 3000K and 4000K colour temperatures. Power 12W, output 1025 lumens (4000K). Non-dimmable. IK03, IP44. Low maintenance with lifespan 90,000 hours L70:B50.





Product Overview

Product name	START Surface IP44 1025lm 830/840 DualTone
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC002892
E-number FI	4170569
Fixture luminous flux (lm)	1025
Luminaire efficacy (lm/W)	85
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	High (>40%)

**START Surface IP44 1025lm 830/840 DualTone
0043426**


Housing colour	White
IP rating	IP44
IK rating	IK03
Product EAN number	5410288434261
Warranty	3 years
Dimming method	N/A

Photometry



START Surface IP44 1025lm 830/840 DualTone
0043426

Technical drawings



Data table

GENERAL DATA

Product name	START Surface IP44 1025lm 830/840 DualTone
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4170569
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	1025
Luminaire efficacy (lm/W)	85

START Surface IP44 1025lm 830/840 DualTone 0043426

Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Distribution type	Diffuse
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	12
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.8
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	65
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	38
Inrush Current (A)	0.5
Inrush Duration (µs)	30
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	High (>40%)
Max. products per 10A C Breaker	60
Max. products per 13A C Breaker	78
Max. products per 16A C Breaker	96
Max. products per 20A C Breaker	120
Max. products per 10A B Breaker	36
Max. products per 13A B Breaker	47
Max. products per 16A B Breaker	58
Max. products per 20A B Breaker	72



START Surface IP44 1025lm 830/840 DualTone
0043426

Connectable conductor cross section - Max (mm²)	2.5
---	-----

LIFETIME DATA

Lifespan L70 B50	90000
Lifespan L80 B50	90000
Lifespan L90 B50	48000

PHYSICAL DATA

Housing colour	White
IP rating	IP44
IK rating	IK03
Diffuser finish	Opal
Diffuser material	Polypropylene
Nominal Product Height (mm)	80
Nominal Product Diameter (mm)	250
Weight (kg)	0.25

PACKAGING

Product EAN number	5410288434261
Packaging single length / height (cm)	25.2
Packaging single width (cm)	8.3
Packaging single depth (cm)	25.2
DUN14 (inner)	15410288434268
Units per outer package	6
Packaging outer length / height (cm)	54.6
Packaging outer width (cm)	28.5
Packaging outer depth (cm)	29.0

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40
Special purpose lamp	No



START Surface IP44 1025lm 830/840 DualTone
0043426

Dry applications use only	No
Suitable for household illumination	No