


START Downlight 5in1 65-185 1750LM
0053149



Features

- START Downlight 5in1 is an integrated LED recessed / surface mounted downlight with built in non dimmable driver. Colour temperature (3000K, 4000K and 6500K) can be adjusted by a 3-way switch located on the back of the fixture. Adaptability to various cut-outs from 65mm to 185mm


Product Overview

Product name	START Downlight 5in1 65-185 1750LM
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting, Ceiling surface mounting
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4278427
Fixture luminous flux (lm)	1750
Luminaire efficacy (lm/W)	97
Light colour	N/A
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	110
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	18
Electrical protection	Class II
Control gear type	LED driver constant current
LED Flickering Rate	Low (6% - 20%)

START Downlight 5in1 65-185 1750LM 0053149

Housing colour	RAL9003
IP rating	IP20
IK rating	IK05
Product EAN number	5410288531496
Warranty	3 years
Dimming method	N/A
Useful luminous flux (#use)	1750

Photometry



Technical drawings

