



Features

- Exterior LED Floodlight, comes complete with 1000mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, integrated anti-condensation valve, IP66, IK08, Class I, 3000K, CRI80, Non-dimmable, 13500lm, 98W, 138lm/W, Asymmetrical Wide beam, 100.000hrs L80B50 lifespan, 374 x 261 x 69mm (LxWxD) dimensions, 2.9kg weight, RAL9017 Traffic Black color, Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3.


Product Overview

Product name	Kalani IP66 14KLM 830 ASYM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Other
General application	Logistics & Industry
ETIM Class	EC001744
E-number FI	4579612
Fixture luminous flux (lm)	13500
Luminaire efficacy (lm/W)	138
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	65x120
Photobiological Risk Group	RG1
Total power consumption (W)	98
Electrical protection	Class I
Control gear type	LED driver constant current

Kalani IP66 14KLM 830 ASYM
0056703


Dimmable	No
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL9017
IP rating	IP66
IK rating	IK08
Product EAN number	5410288567037
Warranty	5 years
Dimming method	N/A

Photometry



Kalani IP66 14KLM 830 ASYM
0056703

Technical drawings



Data table

GENERAL DATA

Product name	Kalani IP66 14KLM 830 ASYM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Other
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001744
E-number FI	4579612
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	13500
Luminaire efficacy (lm/W)	138
Correlated colour temperature (k)	3000
Light colour	Warm White

Kalani IP66 14KLM 830 ASYM 0056703

CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	65x120
Distribution type	Asymmetric
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	98
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	495
Inrush Current (A)	60
Inrush Duration (μ s)	350
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	12
Max. products per 13A C Breaker	16
Max. products per 16A C Breaker	20
Max. products per 20A C Breaker	25
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	12
Max. products per 16A B Breaker	16
Max. products per 20A B Breaker	20
Mains surge immunity (differential mode -> L-N) (kV)	10

Kalani IP66 14KLM 830 ASYM 0056703

Mains surge immunity (common mode -> L/N - GND) (kV)	10
Connectable conductor cross section - Min (mm ²)	1
Connectable conductor cross section - Max (mm ²)	1

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L80 B20	91000

PHYSICAL DATA

Housing colour	RAL9017
IP rating	IP66
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	Glass
Reflector finish	Matt
Nominal Product Length (mm)	374
Nominal Product Width (mm)	261
Nominal Product Height (mm)	69
Weight (kg)	2.9

PACKAGING

Product EAN number	5410288567037
Packaging single length / height (cm)	27.4
Packaging single width (cm)	8.2
Packaging single depth (cm)	38.2
DUN14 (inner)	05410288567037
Units per outer package	1
Packaging outer length / height (cm)	27.4
Packaging outer width (cm)	8.2
Packaging outer depth (cm)	38.2



Kalani IP66 14KLM 830 ASYM
0056703

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-30-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No