

GIOTTO 335 3000K SURFACE EMERGENCY 3034817



















Features

 Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2225lm, 21.6W, 104lm/W, 3000K, CRI 80, non-dimmable, integral 3 hour maintained emergency, 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.

Product Overview


Product name	GIOTTO 335 3000K SURFACE EMERGENCY
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Environment	Indoor
General application	Hospitality, Logistics & Industry
ETIM Class	EC002892
Fixture luminous flux (lm)	2225
Luminaire efficacy (lm/W)	104
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 25




GIOTTO 335 3000K SURFACE EMERGENCY 3034817

Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	144
Luminous flux (emergency) (lm)	144
Total power consumption (W)	21.6
Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971348177
Warranty	5 years
Dimming method	N/A
Colour Code	830

Photometry



Technical drawings



Page 2 of 2