



Features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps
- Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes
- High lumen package - 3150lm
- High lumen efficacy - 150 lm/W
- Switching cycles - 200,000X
- Average life 50,000 hours lifespan
- Lamp length - 1800mm
- Wide beam angle
- High power factor
- Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications
- Suitable for operation with electromagnetic gears / CCG and direct mains operation (220-240V)
- 5-Year warranty


Product Overview

Product name	ToLEDo AVANT T8 CCG 1800 3150LM 865 50K RL
Technology	LED
Lamp shape	Tube, single-ended
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC001959
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Wattage (W)	21
Power consumption (W)	21
Dimmable	No

ToLEDo AVANT T8 CCG 1800 3150LM 865 50K RL
0030296

IP rating	IP20
Product EAN number	5410288302966
Warranty	5 years
Useful luminous flux (#use)	3150

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo AVANT T8 CCG 1800 3150LM 865 50K RL
Technology	LED
Lamp shape	Tube, single-ended
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959

ToLEDo AVANT T8 CCG 1800 3150LM 865 50K RL 0030296

Warranty	5 years
----------	---------

OPTICAL DATA

Useful luminous flux (#use)	3150
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0

ELECTRICAL DATA

Power consumption (W)	21
Wattage (W)	21
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Control gear required	No
Dimmable	No
Inrush Current (A)	18.4
Lamp Energy Label (class)	D

LIFETIME DATA

Lifespan L70 B50	50000
------------------	-------

PHYSICAL DATA

IP rating	IP20
Nominal Product Length (mm)	1777
Nominal Product Diameter (mm)	28
Weight (kg)	0.267

PACKAGING

Product EAN number	5410288302966
Packaging single length / height (cm)	181.5



ToLEDo AVANT T8 CCG 1800 3150LM 865 50K RL
0030296

Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (inner)	15410288302963
Units per outer package	10
Packaging outer length / height (cm)	187.3
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	11.3

SAFETY DATA


Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture

ToLEDo AVANT T8 CCG 1800 3150LM 865 50K RL
0030296

Energy label



0030296




21 kWh/1000h



2019/2015



0030296



21 kWh/1000h



2019/2015