



Features

- Compact and elegant design Suitable replacement for halogen, incandescent and compact fluorescent lamps Instant light at the flick of a switch Uniform light distribution Good colour rendering (CRI 80) Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas Lower maintenance costs 15,000 hours average rated life

Product Overview

Product name	ToLEDo G120 2450LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	20
Lamp shape	Round/globe
Cap/Base	E27
Lamp finish	Opal
Fixture rating	Open
General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC001959
E-number FI	4740656
Luminous flux (lm)	2450
Correlated colour temperature (k)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0



ToLEDo G120 2450LM 840 E27 SL
0026903

Wattage (W)	20
Power consumption (W)	20
Average life (Nominal) (h)	15000
IP rating	IP20
Product EAN number	5410288269030
Warranty	3 years
Colour Code	840
Useful luminous flux (#use)	2450

Technical drawings

