



Features

- X-shape connection unit for opal diffuser version of Otao Linear range, RAL9011 (black) finishing, direct distribution, only 3000K/4000K LED light sources included, feed by next straight luminaire, shipped with 4x fast connectors and additional replacement electrical connectors, 50mm wide extruded aluminium profile, nominal size: 290x290x50x73mm.

Product Overview

|                                   |                                                                                      |
|-----------------------------------|--------------------------------------------------------------------------------------|
| Product name                      | OTAO LINEAR CORN-X OPAL 830/840 BK                                                   |
| Technology                        | LED (3 SDCM)                                                                         |
| Cap/Base                          | N/A                                                                                  |
| Housing                           | Aluminium                                                                            |
| Mount                             | Ceiling recessed mounting, Ceiling surface mounting, Wall surface mounted, Suspended |
| General application               | Office, Education                                                                    |
| ETIM Class                        | EC002556                                                                             |
| Fixture luminous flux (lm)        | 1250                                                                                 |
| Luminaire efficacy (lm/W)         | 128                                                                                  |
| Correlated colour temperature (k) | 4000                                                                                 |
| Light colour                      | Warm White or Neutral White                                                          |
| CRI (Ra)                          | 80                                                                                   |
| Colour Variation Initial (SDCM)   | 3                                                                                    |
| Beam Angle (°)                    | 110                                                                                  |
| Glare control                     | < 28                                                                                 |

OTAO LINEAR CORN-X OPAL 830/840 BK  
0040811

|                             |               |
|-----------------------------|---------------|
| Photobiological Risk Group  | RG0           |
| Total power consumption (W) | 9.8           |
| Electrical protection       | Class III     |
| Dimmable                    | No            |
| Housing colour              | RAL9011       |
| IP rating                   | IP20          |
| IK rating                   | IK03          |
| Product EAN number          | 5410288408118 |
| Warranty                    | 5 years       |
| Dimming method              | N/A           |

Technical drawings

