



Features

- Sensor Dim LED exterior surface mounted luminaire, 1100lm, 12W power consumption, 92lm/W efficacy, 4000K color temperature, CRI80, IP66, IK10, 50,000 hours (L70), white housing, vandal resistant, supplied with anti-theft screws


Product Overview

Product name	START SURFACE IP66 1100LM 840 IK10 MW SENS WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Environment	Indoor, Outdoor
General application	Hospitality
ETIM Class	EC002892
E-number FI	4274705
E-number SE	7505135
Fixture luminous flux (lm)	1100
Luminaire efficacy (lm/W)	92
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	120
Beam Angle (°)	110
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class II

START SURFACE IP66 1100LM 840 IK10 MW SENS WHT
0049291

LED Flickering Rate	High (>40%)
Housing colour	RAL9003
IP rating	IP66
IK rating	IK10
Product EAN number	5410288492919
Warranty	5 years
Dimming method	Other
Colour Code	840
Useful luminous flux (#use)	1100

Photometry



Technical drawings

